# EUROLITE Set EUROLITE LED PAR-64 36x5W + Case sil

**Art. No.: 09000039**

GTIN:











## Features:

**EUROLITE LED PAR-64 RGB 36x5W Short sil**

Bright LED PAR-64 spot with 5 W LEDs

- Operable in stand-alone mode or via DMX
- DMX512 control possible via any commercial DMX controller (occupies 5 channels)
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via rotary control
- Functions: Static colors, RGB color blend, internal programs, adjustable microphone sensitivity, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 36 x 5 W LEDs: 12 x red, 12 x green, 12 x blue
- Beam angle approximately 20°
- Locking possibility at the mounting bracket
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Ready for connection via power cord with safety-plug
- Silver or black housing available

**ROADINGER Flightcase 4x PAR-64 Spot short**

Trunk case, PRO version

- Detachable compartments - case can also be used as universal transport case
- With 4 device compartments

## Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe

## Technical specifications:

| | |
|---|---|
| Weight: | 20.05 kg |

**EUROLITE LED PAR-64 RGB 36x5W Short sil**

| | |
|---|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 145.00 W |
| Dimensions: | Width: 28.5 cm<br>Depth: 26.5 cm<br>Height: 33 cm |
| Weight: | 2.35 kg |
| DMX channels: | 5 |
| DMX connection: | 3-pin XLR |
| Sound-control: | via built-in microphone |
| LED type: | 5 W |
| LED number: | 36 |
| Beam angle: | 20° |
| Dimensions (L x W x H): | 285 x 265 x 330 mm |

**ROADINGER Flightcase 4x PAR-64 Spot short**

| | |
|---|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Device compartment: | 23 cm x 23 cm x 32.5 cm |
| Inside dimensions: | 46 cm x 46 cm x 32.5 cm |
| Dimensions: | Width: 51 cm<br>Depth: 51 cm<br>Height: 41.5 cm |
| Weight: | 10.65 kg |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

## Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.