



The article is no longer in our assortment.

Features:

Logistic

OMNITRONIC RS-602 Recording Mixer

Compact 6-channel studio and live mixer

- Low-noise 6-channel mic/line mixer
- 2 mono inputs with XLR sockets, +48V phantom power and balanced line inputs
- 2 stereo inputs with balanced 6.3 mm jack sockets
- Stereo inputs can also be operated mono
- 3-band EQ for all inputs
- Peak LED per mono input
- Aux send per channel for controlling external effectors
- Stereo aux return with balanced 6.3 mm jack sockets
- Separate main mix, booth and headphones outputs
- Tape inputs assignable to master, booth/headphones
- Precise 10-fold stereo LED meter

OMNITRONIC M-22 Dynamic Microphone

Unidirectional microphone with 3 m jack cable

- Dynamic handheld microphone for studio and stage use
- On/off switch
- Excellent quality at a low price
- 3 m jack cable attached to microphone

- Polar pattern: Cardioid

OMNITRONIC SHP-2000 MK2 DJ Headphones

Convenient DJ stereo headphones

- Closed dynamic stereo headphones for DJs
- 50 mm driver
- Distortion-free playback also at a high volume
- Optimal wearer-comfort due to single cable (L)
- Well-padded, adjustable headband
- Oversized earpieces for screening undesired noise
- Space-saving design with collapsible, rotating (180°) earcups
- Detachable connection cable with gold-plated 3.5 mm stereo jack
- Rugged workmanship for discotheque and stage use
- Incl. 6.3 mm jack adapter and bag

Technical specifications:

Weight:	3.07 kg
---------	---------

OMNITRONIC RS-602 Recording Mixer

Power consumption:	15.00 W
--------------------	---------

Dimensions:	Width: 22 cm
	Depth: 25 cm
	Height: 5.5 cm

Weight:	2.40 kg
---------	---------

Power supply:	2 x 20 V AC, 50/60 Hz
	via included power unit

Inputs:	
2 x mono	XLR or balanced 6.3 mm jack
2 x stereo	balanced 6.3 mm jacks
1 x Aux Return:	balanced 6.3 mm jacks
1 x Tape In	stereo RCA

Outputs:	
1 x Master Out	balanced 6.3 mm jacks
1 x Control Room	balanced 6.3 mm jacks
1 x Aux Send:	balanced 6.3 mm jacks
1 x Tape Out	stereo RCA

Frequency range:	
Microphone:	10-60000 Hz, ±3 dB
Mono:	10-60000 Hz, ±3 dB
Stereo:	10-55000 Hz, ±3 dB
Distortion:	0.01 %
S/N ratio:	112 dB

Tone control/channel:	
Treble:	±15 dB at 12 kHz

Middle:	±15 dB at 2.5 kHz
Bass:	±15 dB at 80 Hz
Dimensions (W x D x H):	220 x 250 x 55 mm

OMNITRONIC M-22 Dynamic Microphone

Type:	Vocal microphone
Capsule type:	Dynamic
Polar pattern:	Cardioid
Frequency range:	50 - 13000 Hz
Sensitivity:	-53 dB
Impedance:	500 Ohm
Connections:	Microphone via 6.3 mm plug (unbal.)
Switch:	On/off switch
Dimensions:	Length: 22 cm Diameter: Ø 5.5 cm
Weight:	0.23 kg
Dimensions:	Length: 300 cm

OMNITRONIC SHP-2000 MK2 DJ Headphones

Cable length:	1.2 m
Frequency range:	20 - 20000 Hz
Sensitivity:	95 dB
Max. SPL:	95 dB
Rated power:	200 mW
Connector type:	3.5 mm jack (stereo); 6.3 mm jack (stereo)
Connections:	Headphones via 6.3 mm jack (stereo) Headphones via 3.5 mm jack (stereo)
Transducer type:	Dynamic
Type (headphones):	Closed
Weight:	0.44 kg

Scope of delivery:

- 1 x adapter cable
- 1 x microphone