

## ALUTRUSS QUADLOCK 6082 TV tower

Art. No.: 09000071

GTIN:



**The article is no longer in our assortment.**

### Features:

### Logistic

#### ALUTRUSS Steel Base Plate round type A

Baseplate for mobile use (connectors 6082 included)

- For the vertical installation of truss elements
- Multifunctional use
- High durability
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair and shop fitting; wedding/gala/events

#### ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

## ALUTRUSS QUADLOCK End Plate QQGP-Male

- Trusspipe: 50 mm
- Made in Europe
- **cone**
- M8 thread

## EUROLITE LCH-36/55M2 Wall mount for monitors

Wall mount

- Wall mount for LCD monitors with a diagonal screen size of 915 mm (36") to 1400 mm (55")
- Adjustable tilting angle
- Stable metal version
- VESA standard
- Mounting materials included in the delivery

## EUROLITE TPC-10 Coupler, silver

Mounting coupler for 50 mm tube, maximum load WLL 150 kg

## ALUTRUSS QUICK-LOCK Spare Pivot with Pin

QUICK-LOCK set

- Accessories for the robust truss system with QUICK-LOCK
- For use with TRI/QUAD system
- Trusspipe: 50 mm
- Made in Europe

## Technical specifications:

---

### ALUTRUSS Steel Base Plate round type A

|             |                                      |
|-------------|--------------------------------------|
| Trusspipe:  | 50 mm                                |
| Material:   | Steel                                |
| Color:      | Alu colored                          |
| Dimensions: | Height: 1.60 cm<br>Diameter: Ø 80 cm |
| Weight:     | 60 kg                                |

### ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

|                             |                                                 |
|-----------------------------|-------------------------------------------------|
| Setup:                      | Easy installation                               |
| Trusspipe:                  | 50 mm x 2 mm                                    |
| Welding technique:          | TIG-welding                                     |
| Welding material:           | AlMg 5                                          |
| Alloy:                      | AlMgSi1 T6 EN-AW 6082 T6 (AlSi1Mg)              |
| Color:                      | Alu colored                                     |
| Strut diameter x thickness: | 16 x 2mm                                        |
| Dimensions:                 | Length: 200 cm<br>Width: 29 cm<br>Height: 29 cm |

|         |          |
|---------|----------|
| Weight: | 10.80 kg |
|---------|----------|

#### ALUTRUSS QUADLOCK End Plate QQGP-Male

|            |             |
|------------|-------------|
| Trusspipe: | 50 mm       |
| Color:     | Alu colored |
| Weight:    | 1.45 kg     |
| Thread:    | M8 thread   |

#### EUROLITE LCH-36/55M2 Wall mount for monitors

|                               |                                                  |
|-------------------------------|--------------------------------------------------|
| Maximum load BGV C1 (8-fold): | 30 kg                                            |
| Maximum load WLL (4-fold):    | 60 kg                                            |
| Distance to wall:             | 75 mm                                            |
| Dimensions:                   | Width: 49.8 cm<br>Depth: 7.5 cm<br>Height: 70 cm |
| Weight:                       | 5.30 kg                                          |
| Interface dimensios:          | 498 x 700 mm                                     |
| Distance to wall:             | 75 mm                                            |
| Dimensions:                   | 748 x 498 x 75 mm                                |

#### EUROLITE TPC-10 Coupler, silver

|                               |                                             |
|-------------------------------|---------------------------------------------|
| Maximum load BGV C1 (8-fold): | 75 kg                                       |
| Maximum load WLL (4-fold):    | 150 kg                                      |
| Tube diameter sector:         | 48 - 50 mm                                  |
| Material:                     | Aluminum                                    |
| Color:                        | Silver                                      |
| Mounting screw:               | M10                                         |
| Dimensions:                   | Length: 10 cm<br>Width: 3 cm<br>Depth: 9 cm |
| Weight:                       | 0.16 kg                                     |

#### ALUTRUSS QUICK-LOCK Spare Pivot with Pin

|            |             |
|------------|-------------|
| Trusspipe: | 50 mm       |
| Color:     | Alu colored |
| Weight:    | 0.09 kg     |

#### Scope of delivery:

##### 1 x ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

1 x connection set

**4 x ALUTRUSS QUICK-LOCK Spare Pivot with Pin**

2 x splint

2 x bolt