



Features:

Logistic

EUROLITE LED PAR-64 RGBA 10mm Short sil

PRO spotlight as LED DMX model

- 4 or 6 DMX channels selectable for numerous applications
- Equipped with 177 x 10 mm LEDs: 30 x red, 48 x green, 54 x blue and 45 x amber
- Sound-control via built-in microphone
- Beam angle approximately 36°
- Locking possibility at the mounting bracket
- Addressing and setting via control panel with LED display
- Preset (internal programs)
- RGBA color change
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Dimmer and Strobe settings via DMX
- Ready for connection with power cord and plug
- Also available as floor spot version
- Available in silver or black
- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX512 control via regular DMX controller
- Can be operated in 6; 4 CH mode
- Control via stand-alone; DMX

EUROLITE DMX LED Operator 2 controller

Compact DMX controller for easy application

- 8 control channels only suitable for special LED-spots (RGBA and RGBW)
- Select color mode for choosing single colors
- Internal programs
- Auto mode for running all programs
- Sound-control via built-in microphone
- Pause function
- Blackout function
- Control LEDs display current operating mode
- Program Select-fader for selecting the internal programs
- Speed-fader for adjusting the program-speed
- Strobe-effect with adjustable speed
- Additional fogger button for direct control of a DMX smoke machine (CH-7/8)
- Designed for standing operation, optional installation is customer's choice
- Suitable for 254 mm racks (10") with 4 units
- Power supply via enclosed 12 V DC power unit
- Can transmit up to 8 DMX channels
- Control via DMX; sound to light via microphone
- Desktop console housing

OMNITRONIC XLR Cable 3-pin 5m bk

Audio cable with 3-pin XLR connectors

Technical specifications:

Weight:	11.29 kg
---------	----------

EUROLITE LED PAR-64 RGBA 10mm Short sil

Power supply:	230 V AC, 50 Hz
Power consumption:	27 W
Lamp type:	LED lamp
DMX channels:	6; 4
Control:	Stand-alone; DMX
Fixtures available for:	Light´J; LED PC-Control 512
Beam angle (1/2 peak):	36°
Housing color:	Silver
Dimensions:	Width: 26 cm Depth: 27 cm Height: 39 cm
Weight:	2.30 kg
DMX channels:	4/6
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED number:	177
LED type:	10 mm
Beam angle:	36°

Dimensions:	260 x 270 x 390 mm
EUROLITE DMX LED Operator 2 controller	
Pin configuration:	Inside + / outside -
Power consumption:	4.00 W
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
DMX channels:	Output 8
Control:	DMX; sound to light via microphone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 26.5 cm Depth: 16.5 cm Height: 5.5 cm
Weight:	1.12 kg
Power supply:	230 V AC, 50 Hz, via 12 V DC, 300 mA power unit included in the delivery
DMX512 output:	3-pin XLR connector

OMNITRONIC XLR Cable 3-pin 5m bk

Cable construction:	2 x 0.22 mm² microphone cable
Cable length:	5 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	0.24 kg
Material:	Metal

Scope of delivery:

1 x XLR cable