



Features:

Logistic

ALUTRUSS Base Plate BP-30 80x80

Baseplate for mobile use (connectors 6082 included)

- For the vertical installation of truss elements
- Multifunctional use
- High durability
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair and shop fitting; wedding/gala/events

ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

ALUTRUSS QUADLOCK End Plate QQGP

Robust truss system

- High stability
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Easy installation as the cross-beams do no longer need to be screwed on
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school

EXPAND XPTC20W Truss Cover 200cm white

Flexible truss cover

- Best suited for reproducing light projections
- Extremely stretchable cloth
- Washable (needs to be treated with flame retardant spray afterwards)
- Suitable for all 3- or 4-point systems with 30 cm side length
- Made in Germany
- For application areas such as: Wedding/gala/events; Trade fair and shop fitting

EUROLITE LED B-40 Beam effect

Mirror ball effect with 3in1 color mixture

- Ball with 124 lenses
- Equipped with 5 x 4 W TCL LEDs (tri-color)
- Particularly bright illuminating power of the LED
- Up to 14 rotations per minute
- Sound controlled via built-in microphone
- Microphone-sensitivity adjustable via rotary-control
- Strobe effect
- Auto mode
- Internal program
- Programmable color-change speed and strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Innumerable uses
- When smoke is used, this effect becomes especially attractive
- Ideal for bands, stages or solo entertainers
- Hanging or standing installation possible
- Mounting bracket for installation on a truss system included
- Ready for connection with power cord and safety-plug
- Addressing and setting via control panel with 4-digit LED display and three operating buttons
- DMX512 control via regular DMX controller
- Control via stand-alone

Technical specifications:

Weight:	45.14 kg
---------	----------

ALUTRUSS Base Plate BP-30 80x80

Trusspipe:	50 mm
------------	-------

Material:	Steel
-----------	-------

Color:	Alu colored
--------	-------------

Dimensions:	Width: 80 cm
-------------	--------------

	Depth: 80 cm
	Height: 0.60 cm
Weight:	28.60 kg

ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi1 T6 EN-AW 6082 T6 (AlSi1Mg)
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 200 cm Width: 29 cm Height: 29 cm
Weight:	10.80 kg

ALUTRUSS QUADLOCK End Plate QQGP

Setup:	Easy installation
Trusspipe:	50 mm
Color:	Alu colored
Weight:	2.05 kg

EXPAND XPTC20W Truss Cover 200cm white

Color:	White
Dimensions:	Length: 200 cm
Weight:	0.39 kg

EUROLITE LED B-40 Beam effect

Power supply:	230 V AC, 50 Hz
Power consumption:	30.00 W
Lamp type:	LED lamp
Control:	Stand-alone
Fixtures available for:	Light´J
Housing color:	Black
Dimensions:	Width: 32 cm Depth: 32 cm Height: 38 cm
Weight:	3.30 kg
Rotation-speed:	approx. 14 RPM
LED type:	4 W TCL

LED number:	5
Sound-control:	via built-in microphone
DMX channels:	4
DMX connection:	3-pin XLR
Dimensions (L x W x H):	320 x 320 x 380 mm

Scope of delivery:

1 x connection set