



Features:

Logistic

EUROLITE LED PAR-56 COB RGB 100W sil

PRO spotlight as DMX model with COB LED

- Equipped with a powerful RGB 100 W COB LED
- Functions: static colors, RGB color mixture, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Dimmer speed (step response) adjustable
- Operable in stand-alone mode or with DMX interface
- Adjustable microphone sensitivity via LCD display
- Comfortable addressing and setting via control panel with LCD display and four operating buttons
- Locking possibility at the mounting bracket
- With color filter frame
- Ready for connection via power cord with safety-plug
- Available in silver or in black
- 1 LED 100 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
- Strobe effect
- Can be operated in 3; 5 CH mode
- Control via DMX; sound to light via microphone
- With a beam angle of 40°
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE TB-4X T-Bar

For problem-free installations

- Makes the installation of your lighting system really easy
- Fully wired with DMX-splitter
- 1.50 meters
- With 4 spot connections
- With 4 flap safety-plugs
- With 4 DMX connectors
- Connection via Powercon In/Out-socket

Technical specifications:

Weight:	15.10 kg
---------	----------

EUROLITE LED PAR-56 COB RGB 100W sil

Power supply:	230 V AC, 50 Hz
Power consumption:	130 W
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
DMX channels:	3; 5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone
Fixtures available for:	EASY SHOW 1; LED PC-Control 512; Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	40°
Beam angle (1/2 peak):	40°
Housing color:	Silver
Dimensions:	Width: 24 cm Depth: 36.5 cm Height: 31.5 cm
Weight:	2.6 kg

EUROLITE TB-4X T-Bar

Power supply:	230 V AC, 50 Hz
Output current:	Max. 10 A per channel
Dimensions:	Length: 150 cm Width: 7.5 cm Height: 16.5 cm
Weight:	4.70 kg

Max. power output:	2300 W
Max. total current:	10 A
Max. output/channel:	2300 W
Max. current/channel:	10 A
Maximum load per fixation point:	7.5 kg
Max. spaced braceload:	30 kg
Dimensions (L x W x H):	1500 x 75 x 165 mm

Scope of delivery: