

FUTURELIGHT Set 2x EYE-7 BEAM

4in1 moving head beam with 15 W LEDs

Art. No.: 09000234

GTIN:



Features:

- Equipped with 7 x 15 W quadcolor LED with RGBW colors (Osram)
- Compact housing
- Narrow illumination angle
- High PAN/TILT speed
- Supports RDM (Remote Device Management)
- 14, 16 or 22 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity and colors
- Master dimmer
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device

Logistic

- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller

Technical specifications:

Weight:	12.80 kg
---------	----------

FUTURELIGHT EYE-7 RGBW LED Moving-Head Beam

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

Power consumption:	100.00 W
--------------------	----------

Dimensions:	Width: 17.9 cm Depth: 35 cm Height: 24.4 cm
-------------	---

DMX channels:	14/16/22
---------------	----------

DMX connection:	3-pin XLR
-----------------	-----------

Sound-control:	via built-in microphone
----------------	-------------------------

Flash-rate:	18 Hz
-------------	-------

LED number:	7
-------------	---

LED type:	15 W QCL
-----------	----------

Beam angle:	7°
-------------	----

Maximum PAN-movement:	630°
-----------------------	------

Maximum TILT-movement:	270°
------------------------	------

Dimensions (L x W x H):	244 x 179 x 350 mm
-------------------------	--------------------

Weight:	6 kg
---------	------

Scope of delivery:
