



Features:

Logistic

OMNILUX PAR-64 240V/1000W GX16d NSP 300h H

PAR-64 lamp (Halogen)

- Harmless for color-foils
- The heat permeates the front-glass continuously
- Dimmable
- Very high color rendering index (CRI)

EUROLITE PAR-64 Spot Long with Cable sil

Long PAR-64 housing (with open cable ends)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Strong cable tension relief
- With mounting bracket
- Available in various colors
- For PAR 64
- For application areas such as: Advertisement/Shop window; decoration; clubs/dancing school

Technical specifications:

Weight:	3.17 kg
---------	---------

OMNILUX PAR-64 240V/1000W GX16d NSP 300h H

Operating voltage:	240 V, 220 - 240 V
Nominal wattage:	1000 W
Base:	GX16d
Lamp type:	Incandescent lamp; halogen lamp; reflector lamp
Lamp specification:	Dimmable
Beam angle:	11°
Color of light:	White
Color temperature:	3000K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	PAR-64
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	300 h
Luminous flux:	18700 lm
Dimensions (LxD):	152x203 mm
Weight:	0.77 kg
EPREL-Nr:	1509965

EUROLITE PAR-64 Spot Long with Cable sil

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 1000 W
Protection class:	Protection class I
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.7 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame (optional)
Housing color:	Silver
Attachment system:	Mounting bracket
Slot for spot length:	25.7 cm x 25.7 cm
Dimensions:	Length: 41.5 cm Width: 26.5 cm Height: 34.5 cm

Weight:	1.63 kg
Dimensions:	Length: 25.5 cm
	Width: 25.5 cm
	Diameter: Ø 20.2 cm

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x lamp clamping ring
- 1 x user manual