



**The article is no longer in our assortment.**

### Features:

### Logistic

#### EUROLITE PAR-64 Spot Long with Cable bk

Long PAR-64 housing (with open cable ends)

- Durable aluminum cabinet
- Strong aluminum mounting bracket
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Blackened tube for precise light output
- Strong brass clamps with extension spring for safe hold and for quick opening of the rear housing cover
- Protection grille on the rear housing cover - complies with CE regulations
- Comes fully-wired with black silicone cable, stable earthing in the housing and directly clamped ceramic socket
- Color filter frame included in delivery
- Strong cable tension relief
- Well-suited for easy installation of our Raylight reflectors with matching connector (GX16)
- Simple mounting: connect with ceramic socket - ready!
- Power plug has to be ordered separately; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends

- For PAR 64

#### OMNILUX PAR-64 240V/1000W GX16d NSP 300h H

PAR-64 lamp (Halogen)

- Harmless for color-foils
- The heat permeates the front-glass continuously
- Dimmable
- Very high color rendering index (CRI)

#### Technical specifications:

|         |         |
|---------|---------|
| Weight: | 3.51 kg |
|---------|---------|

#### EUROLITE PAR-64 Spot Long with Cable bk

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Power supply:         | 230 V AC, 50 Hz                                          |
| Power consumption:    | Max. 1000 W                                              |
| Protection class:     | Protection class I                                       |
| Power connection:     | Fixed supply cord with open wires                        |
| Cable length:         | Approx. 0.7 m                                            |
| Base:                 | GX16d                                                    |
| Lamp type:            | Selectable                                               |
| Color generation:     | Via color filter frame (optional)                        |
| Housing color:        | Black                                                    |
| Slot for spot length: | 25.7 cm x 25.7 cm                                        |
| Dimensions:           | Length: 42.5 cm<br>Width: 26.5 cm<br>Height: 27 cm       |
| Weight:               | 1.97 kg                                                  |
| Dimensions:           | Length: 25.5 cm<br>Width: 25.5 cm<br>Diameter: Ø 20.2 cm |

#### OMNILUX PAR-64 240V/1000W GX16d NSP 300h H

|                              |                                                 |
|------------------------------|-------------------------------------------------|
| Operating voltage:           | 240 V, 220 - 240 V                              |
| Nominal wattage:             | 1000 W                                          |
| Base:                        | GX16d                                           |
| Lamp type:                   | Incandescent lamp; halogen lamp; reflector lamp |
| Lamp specification:          | Dimmable                                        |
| Beam angle:                  | 11°                                             |
| Color of light:              | White                                           |
| Color temperature:           | 3000K                                           |
| Color rendering index (CRI): | 95 Ra                                           |
| Lead time:                   | 0 s                                             |

|                             |                  |
|-----------------------------|------------------|
| Construction:               | PAR-64           |
| Operating temperature max.: | 40° C            |
| Operating temperature min.: | 20° C            |
| Burning position:           | S180 (universal) |
| Lamp life:                  | 300 h            |
| Luminous flux:              | 18700 lm         |
| Dimensions (LxD):           | 152x203 mm       |
| Weight:                     | 0.77 kg          |
| EPREL-Nr:                   | 1509965          |

**Scope of delivery:**

- 1 x spotlight
- 1 x filter frame
- 1 x lamp clamping ring
- 1 x user manual