



Features:

Logistic

EUROLITE PAR-20 Spot silver

PAR-20 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Strong cable tension relief
- Control via plug and play
- With mounting bracket
- Available in various colors
- For PAR 20
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window

OMNILUX PAR-20 240V/75W E-27 spot

PAR-20 lamp

- Halogene lamp, suitable for E-27-socket (230 V~)
- Clear, brilliant halogene light for spot (10°) or Flood (30°)
- Operation at mains voltage without transformator
- Front screen provides for low bleaching and protects against contact with and soiling of burner

- Easy replacement with normal E-27 reflector lamps
- Average lifetime 1500 hours
- Constant light flow and no blackening of the burner during lifetime
- Any burner position possible
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

Technical specifications:

Weight:	0.42 kg
---------	---------

EUROLITE PAR-20 Spot silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0.4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-20
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	8.5 cm x 8.5 cm
Dimensions:	Width: 15 cm Depth: 18 cm Height: 11.2 cm Diameter: Ø 8 cm
Weight:	0.32 kg
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Material:	Aluminum
Dimensions:	Length: 8.4 cm Width: 8.4 cm Diameter: Ø 6.1 cm

OMNILUX PAR-20 240V/75W E-27 spot

Voltage (lamps):	240 V, AC
Nominal wattage:	75 W
Base:	E27

Lamp type:	Halogen lamp; clear lamp; high voltage lamp; reflector lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	10°
Color of light:	White
Color temperature:	2800K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	PAR-20
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	1500 h
Luminous flux:	725 lm
Wavelength:	585 nm
Lamp current:	0.31 A
Dimensions (LxD):	86x64 mm

Scope of delivery:

1 x spotlight
1 x filter frame
1 x user manual