



### Features:

### Logistic

#### EUROLITE PAR-30 Spot silver

#A#1002\_0\_0# housing with #A#1003\_0\_0# socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget

#### OMNILUX PAR-30 240V/100W E-27 spot

PAR-30 lamp

- Halogene lamp, suitable for E-27-socket (230 V~)
- Clear, brilliant halogene light for spot (10°) or Flood (30°)
- Operation at mains voltage without transformer
- Front screen provides for low bleaching and protects against contact with and soiling of burner
- Easy replacement with normal E-27 reflector lamps
- Average lifetime 2000 hours
- Constant light flow and no blackening of the burner during lifetime
- Any burner position possible
- Dimmable

- Hot restrike
- Very high color rendering index (CRI)

Technical specifications:

|         |         |
|---------|---------|
| Weight: | 0.63 kg |
|---------|---------|

OMNILUX PAR-30 240V/100W E-27 spot

|                              |                                                                           |
|------------------------------|---------------------------------------------------------------------------|
| Voltage (lamps):             | 240 V, AC                                                                 |
| Nominal wattage:             | 100 W                                                                     |
| Base:                        | E27                                                                       |
| Lamp type:                   | Halogen lamp; clear lamp; high voltage lamp; reflector lamp; halogen bulb |
| Lamp specification:          | Dimmable<br>Hot restrike                                                  |
| Beam angle:                  | 10°                                                                       |
| Color of light:              | White                                                                     |
| Color temperature:           | 2700K                                                                     |
| Color rendering index (CRI): | 95 Ra                                                                     |
| Lead time:                   | 0 s                                                                       |
| Construction:                | PAR-30                                                                    |
| Operating temperature max.:  | 40° C                                                                     |
| Operating temperature min.:  | 20° C                                                                     |
| Burning position:            | S180 (universal)                                                          |
| Lamp life:                   | 2000 h                                                                    |
| Luminous flux:               | 800 lm                                                                    |
| Dimensions (LxD):            | 92x95 mm                                                                  |

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x user manual