



Features:

Logistic

EUROLITE PAR-56 Lite Spot

PAR-56 spot in steel sheet housing

- Ideal for small discotheques or compact lighting-systems for bands
- Delivery includes silicone-cable and color filter frame
- Fourth snap-clamp for the color-filter-frame
- Protection grille on the rear housing cover - complies with CE-regulations
- For permanent installations or road-use
- For PAR-56 lamps
- Different radiation angles possible (spot, medium or flood)
- For PAR 56

OMNILUX PAR-56 230V/300W NSP 2000h H

Special lamp for show effect lighting

- Dimmable
- Very high color rendering index (CRI)

Technical specifications:

Weight:	14.27 kg
---------	----------

EUROLITE PAR-56 Lite Spot

Power supply:	230 V AC, 50 Hz
Power consumption:	310 W
Housing color:	Black
Dimensions:	Width: 21.5 cm Depth: 23.5 cm Height: 24 cm
Weight:	1.25 kg
Dimensions (L x W x H):	240 x 215 x 235 mm

OMNILUX PAR-56 230V/300W NSP 2000h H

Operating voltage:	230 V
Nominal wattage:	300 W
Base:	GX16d
Lamp type:	Incandescent lamp; halogen lamp; reflector lamp
Lamp specification:	Dimmable
Beam angle:	10°
Color of light:	White
Color temperature:	2800K
Color rendering index (CRI):	99.3 Ra
Lead time:	0.5 s
Construction:	PAR-56
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Candle power:	45000 cd
Luminous flux:	3500 lm
Wavelength:	778 nm
Dimensions (LxD):	127x178 mm
Weight:	0.56 kg
EPREL-Nr:	1273391

Scope of delivery: