



Features:

Logistic

EUROLITE PAR-56 Spot Long with Cable bk

Long PAR-56 housing (with open cable ends)

- Rugged metal housing
- Blackened tube for precise light output
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Strong extension spring for safe hold and for quick opening of the rear housing cover
- Strong cable tension relief
- With mounting bracket
- For PAR 56

EUROLITE Raylight PAR-56,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-56 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

OMNILUX A1 230V/500W GY-9.5 75h

Special lamp for show effect lighting

- One-sided base
- Easy lamp replacement
- Dimmable
- Very high color rendering index (CRI)

Technical specifications:

Weight:	1.46 kg
---------	---------

EUROLITE PAR-56 Spot Long with Cable bk

Power supply:	230 V AC, 50 Hz
---------------	-----------------

Power consumption:	Max. 500 W
--------------------	------------

Protection class:	Protection class I
-------------------	--------------------

Power connection:	Fixed supply cord with open wires
-------------------	-----------------------------------

Cable length:	Approx. 0.7 m
---------------	---------------

Base:	GX16d
-------	-------

Lamp type:	Selectable
------------	------------

Color generation:	Via color filter frame
-------------------	------------------------

Housing color:	Black
----------------	-------

Attachment system:	Mounting bracket
--------------------	------------------

Dimensions:	Length: 36 cm Width: 23 cm Height: 23.5 cm
-------------	--

Weight:	1.30 kg
---------	---------

Dimensions:	Length: 22.5 cm Width: 22.5 cm Diameter: Ø 17.6 cm
-------------	--

EUROLITE Raylight PAR-56,GY-9.5 Socket long

Power supply:	230 V AC, 50 Hz
---------------	-----------------

Power consumption:	500 W
--------------------	-------

Base:	GY9.5; GX16d
-------	--------------

Beam angle (1/2 peak):	NSP
------------------------	-----

Color:	Alu colored
--------	-------------

Dimensions:	Diameter: Ø 17.5 cm
-------------	---------------------

Weight:	0.12 kg
---------	---------

OMNILUX A1 230V/500W GY-9.5 75h

Voltage (lamps):	230 V, AC
------------------	-----------

Nominal wattage:	500 W
Base:	GY9.5
Lamp type:	Halogen lamp
Lamp specification:	Dimmable
Beam angle:	310°
Color of light:	White
Color temperature:	2700K
Color rendering index (CRI):	100 Ra
Lead time:	0.2 s
Construction:	Bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	75 h
Luminous flux:	7200 lm
Wavelength:	778 nm
Lamp current:	2.17 A
Dimensions (LxD):	78x18 mm
Weight:	0.02 kg
Energy efficiency class (A - G):	G
EPREL-Nr:	1519666

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x lamp clamping ring
- 1 x user manual