



The article is no longer in our assortment.

Features:

Logistic

EUROLITE PAR-56 Spot Long with Cable sil

Long PAR-56 housing (with open cable ends)

- Durable aluminum cabinet
- Strong aluminum mounting bracket
- Blackened tube for precise light output
- Color filter frame included in delivery
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Strong extension spring for safe hold and for quick opening of the rear housing cover
- Protection grille on the rear housing cover - complies with CE regulations
- Comes fully-wired with black silicone cable, stable earthing in the housing and directly clamped ceramic socket
- Strong cable tension relief
- Well-suited for easy installation of our Raylight reflectors with matching connector (GX16)
- Simple mounting: connect with ceramic socket - ready!
- Power plug has to be ordered separately; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends
- For PAR 56

GE PAR-56 240V/300W NSP 2000h

- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	1.87 kg
---------	---------

EUROLITE PAR-56 Spot Long with Cable sil

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
Protection class:	Protection class I
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.7 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame
Housing color:	Silver
Dimensions:	Length: 36 cm Width: 23 cm Height: 23.5 cm
Weight:	1.28 kg
Dimensions:	Length: 22.5 cm Width: 22.5 cm Diameter: Ø 17.6 cm

GE PAR-56 240V/300W NSP 2000h

Voltage (lamps):	240 V, AC
Nominal wattage:	300 W
Base:	GX16d
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; reflector lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	19°
Color of light:	White
Color temperature:	2750K
Color rendering index (CRI):	95 Ra
Lead time:	0 s

Construction:	PAR-56
Operating temperature max.:	40° C
Operating temperature min.:	10° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	3450 lm
Dimensions (LxD):	127x178 mm
Weight:	0.59 kg

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x lamp clamping ring
- 1 x user manual