



The article is no longer in our assortment.

Features:

Logistic

EUROLITE PAR-56 Spot Short with Cable bk

PAR-56 housing with silicone cable and open cable ends

- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Blackened tube for precise light output
- Strong cable tension relief
- With mounting bracket
- For PAR 56

EUROLITE Raylight PAR-56,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-56 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

GE M38 240V/300W GY-9.5 2000h

Studio-lamp for base GY9.5

- One-sided base
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	0.95 kg
---------	---------

EUROLITE PAR-56 Spot Short with Cable bk

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/500 W PAR-56
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.8 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Aluminum
Dimensions:	Length: 26 cm Width: 23.5 cm Height: 22 cm
Weight:	0.81 kg
Diameter mounting holes:	2 x Ø12mm
Material:	Metal, 2 mm
Diameter mounting holes:	2 x Ø8mm
Grid size:	10 x 10 mm
Dimensions:	Length: 21.5 cm Width: 21.5 cm Diameter: Ø 17.1 cm

EUROLITE Raylight PAR-56,GY-9.5 Socket long

Power supply:	230 V AC, 50 Hz
Power consumption:	500 W
Base:	GY9.5; GX16d

Beam angle (1/2 peak):	NSP
Color:	Alu colored
Dimensions:	Diameter: Ø 17.5 cm
Weight:	0.12 kg

GE M38 240V/300W GY-9.5 2000h

Voltage (lamps):	240 V, AC
Nominal wattage:	300 W
Base:	GY9.5
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	310°
Color of light:	White
Color temperature:	2900K
Color rendering index (CRI):	100 Ra
Construction:	Bi pin
Operating temperature max.:	40° C
Operating temperature min.:	10° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	5500 lm
Dimensions (LxD):	80x29 mm
Weight:	0.02 kg

Scope of delivery:

1 x spotlight
 1 x filter frame
 1 x lamp clamping ring
 1 x user manual