



### Features:

### Logistic

#### EUROLITE PAR-56 Spot Short with Cable bk

PAR-56 housing with silicone cable and open cable ends

- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Blackened tube for precise light output
- Strong cable tension relief
- With mounting bracket
- For PAR 56

#### EUROLITE Raylight PAR-56,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-56 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

**GE M38 240V/300W GY-9.5 2000h**

Studio-lamp for base GY9.5

- One-sided base
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

**Technical specifications:**

|         |         |
|---------|---------|
| Weight: | 0.95 kg |
|---------|---------|

**EUROLITE PAR-56 Spot Short with Cable bk**

|                          |                                                          |
|--------------------------|----------------------------------------------------------|
| Power supply:            | 230 V AC, 50 Hz                                          |
| Power consumption:       | Max. 500 W                                               |
| Protection class:        | Protection class I                                       |
| Suitable lamp:           | Max. 230 V/500 W PAR-56                                  |
| Power connection:        | Fixed supply cord with open wires                        |
| Cable length:            | Approx. 0.8 m                                            |
| Base:                    | GX16d                                                    |
| Lamp type:               | Selectable                                               |
| Color generation:        | Via color filter frame                                   |
| Housing color:           | Black                                                    |
| Attachment system:       | Mounting bracket                                         |
| Material:                | Aluminum                                                 |
| Dimensions:              | Length: 26 cm<br>Width: 23.5 cm<br>Height: 22 cm         |
| Weight:                  | 0.81 kg                                                  |
| Diameter mounting holes: | 2 x Ø12mm                                                |
| Material:                | Metal, 2 mm                                              |
| Diameter mounting holes: | 2 x Ø8mm                                                 |
| Grid size:               | 10 x 10 mm                                               |
| Dimensions:              | Length: 21.5 cm<br>Width: 21.5 cm<br>Diameter: Ø 17.1 cm |

**EUROLITE Raylight PAR-56,GY-9.5 Socket long**

|                    |                 |
|--------------------|-----------------|
| Power supply:      | 230 V AC, 50 Hz |
| Power consumption: | 500 W           |
| Base:              | GY9.5; GX16d    |

|                        |                     |
|------------------------|---------------------|
| Beam angle (1/2 peak): | NSP                 |
| Color:                 | Alu colored         |
| Dimensions:            | Diameter: Ø 17.5 cm |
| Weight:                | 0.12 kg             |

#### GE M38 240V/300W GY-9.5 2000h

|                              |                                                           |
|------------------------------|-----------------------------------------------------------|
| Voltage (lamps):             | 240 V, AC                                                 |
| Nominal wattage:             | 300 W                                                     |
| Base:                        | GY9.5                                                     |
| Lamp type:                   | Halogen lamp; clear lamp; high voltage lamp; halogen bulb |
| Lamp specification:          | Dimmable<br>Hot restrike                                  |
| Beam angle:                  | 310°                                                      |
| Color of light:              | White                                                     |
| Color temperature:           | 2900K                                                     |
| Color rendering index (CRI): | 100 Ra                                                    |
| Construction:                | Bi pin                                                    |
| Operating temperature max.:  | 40° C                                                     |
| Operating temperature min.:  | 10° C                                                     |
| Burning position:            | S180 (universal)                                          |
| Lamp life:                   | 2000 h                                                    |
| Luminous flux:               | 5500 lm                                                   |
| Dimensions (LxD):            | 80x29 mm                                                  |
| Weight:                      | 0.02 kg                                                   |

#### Scope of delivery:

1 x spotlight  
 1 x filter frame  
 1 x lamp clamping ring  
 1 x user manual