



Features:

Logistic

EUROLITE PAR-64 Spot Long with Cable sil

Long PAR-64 housing (with open cable ends)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Strong cable tension relief
- With mounting bracket
- Available in various colors
- For PAR 64
- For application areas such as: Advertisement/Shop window; decoration; clubs/dancing school

GE CP60 SUPER PAR 64 240V/1000W VNSP 300h

- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	2.56 kg
---------	---------

EUROLITE PAR-64 Spot Long with Cable sil

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 1000 W
Protection class:	Protection class I
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.7 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame (optional)
Housing color:	Silver
Attachment system:	Mounting bracket
Slot for spot length:	25.7 cm x 25.7 cm
Dimensions:	Length: 41.5 cm Width: 26.5 cm Height: 34.5 cm
Weight:	1.63 kg
Dimensions:	Length: 25.5 cm Width: 25.5 cm Diameter: Ø 20.2 cm

GE CP60 SUPER PAR 64 240V/1000W VNSP 300h

Voltage (lamps):	240 V, AC
Nominal wattage:	1000 W
Base:	GX16d
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; reflector lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	15°
Color of light:	White
Color temperature:	3200K
Color rendering index (CRI):	100 Ra
Lead time:	0 s
Construction:	PAR-64
Operating temperature max.:	40° C
Operating temperature min.:	10° C
Burning position:	S180 (universal)

Lamp life:	300 h
Dimensions (LxD):	152x203 mm
Weight:	0.93 kg

- Scope of delivery:**
- 1 x spotlight
 - 1 x filter frame
 - 1 x lamp clamping ring
 - 1 x user manual