EUROLITE PAR-56 Short spot + PAR 56 GE! set, black

Art. No.: 09000487

GTIN:





Features:

EUROLITE PAR-56 Spot Short with Cable bk

PAR-56 housing with silicone cable and open cable ends

- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Blackened tube for precise light output
- Strong cable tension relief
- With mounting bracket
- For PAR 56

GE PAR-56 240V/300W NSP 2000h

- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Weight:	1.40 kg

EUROLITE PAR-56 Spot Short with Cable bk

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/500 W PAR-56
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.8 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Aluminum
Dimensions:	Length: 26 cm Width: 23.5 cm Height: 22 cm
Weight:	0.81 kg
Diameter mounting holes:	2 x Ø12mm
Material:	Metal, 2 mm
Diameter mounting holes:	2 x Ø8mm
Grid size:	10 x 10 mm
Dimensions:	Length: 21.5 cm Width: 21.5 cm Diameter: Ø 17.1 cm

GE PAR-56 240V/300W NSP 2000h

Voltage (lamps):	240 V, AC
Nominal wattage:	300 W
Base:	GX16d
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; reflector lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	19°
Color of light:	White
Color temperature:	2750K
Color rendering index (CRI):	95 Ra

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lead time:	0 s
Construction:	PAR-56
Operating temperature max.:	40° C
Operating temperature min.:	10° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Candle power:	40000 cd
Luminous flux:	3450 lm
Dimensions (LxD):	127x178 mm
Weight:	0.59 kg

Scope of delivery:

1 x spotlight
1 x filter frame
1 x lamp clamping ring
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.