



### Features:

### Logistic

#### EUROLITE PAR-56 Spot Short with Cable bk

PAR-56 housing with silicone cable and open cable ends

- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Blackened tube for precise light output
- Strong cable tension relief
- With mounting bracket
- For PAR 56

#### EUROLITE Raylight PAR-56,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-56 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

**OMNILUX 230V/300W GY-9.5 180h**

Studio-lamp for base GY9.5

- One-sided base
- Dimmable
- Very high color rendering index (CRI)

**Technical specifications:**

|         |         |
|---------|---------|
| Weight: | 0.95 kg |
|---------|---------|

**EUROLITE PAR-56 Spot Short with Cable bk**

|                          |                                                          |
|--------------------------|----------------------------------------------------------|
| Power supply:            | 230 V AC, 50 Hz                                          |
| Power consumption:       | Max. 500 W                                               |
| Protection class:        | Protection class I                                       |
| Suitable lamp:           | Max. 230 V/500 W PAR-56                                  |
| Power connection:        | Fixed supply cord with open wires                        |
| Cable length:            | Approx. 0.8 m                                            |
| Base:                    | GX16d                                                    |
| Lamp type:               | Selectable                                               |
| Color generation:        | Via color filter frame                                   |
| Housing color:           | Black                                                    |
| Attachment system:       | Mounting bracket                                         |
| Material:                | Aluminum                                                 |
| Dimensions:              | Length: 26 cm<br>Width: 23.5 cm<br>Height: 22 cm         |
| Weight:                  | 0.81 kg                                                  |
| Diameter mounting holes: | 2 x Ø12mm                                                |
| Material:                | Metal, 2 mm                                              |
| Diameter mounting holes: | 2 x Ø8mm                                                 |
| Grid size:               | 10 x 10 mm                                               |
| Dimensions:              | Length: 21.5 cm<br>Width: 21.5 cm<br>Diameter: Ø 17.1 cm |

**EUROLITE Raylight PAR-56,GY-9.5 Socket long**

|                        |                 |
|------------------------|-----------------|
| Power supply:          | 230 V AC, 50 Hz |
| Power consumption:     | 500 W           |
| Base:                  | GY9.5; GX16d    |
| Beam angle (1/2 peak): | NSP             |
| Color:                 | Alu colored     |

|             |                     |
|-------------|---------------------|
| Dimensions: | Diameter: Ø 17.5 cm |
| Weight:     | 0.12 kg             |

**OMNILUX 230V/300W GY-9.5 180h**

|                                  |                                 |
|----------------------------------|---------------------------------|
| Operating voltage:               | 230 V, 220 - 240 V              |
| Nominal wattage:                 | 300 W                           |
| Base:                            | GY9.5                           |
| Lamp type:                       | Incandescent lamp; halogen lamp |
| Lamp specification:              | Dimmable                        |
| Beam angle:                      | 310°                            |
| Color of light:                  | White                           |
| Color temperature:               | 2800K                           |
| Color rendering index (CRI):     | 95 Ra                           |
| Lead time:                       | 0 s                             |
| Construction:                    | Bi pin                          |
| Operating temperature max.:      | 40° C                           |
| Operating temperature min.:      | 20° C                           |
| Burning position:                | S180 (universal)                |
| Lamp life:                       | 180 h                           |
| Luminous flux:                   | 3800 lm                         |
| Dimensions (LxD):                | 65x16 mm                        |
| Weight:                          | 0.02 kg                         |
| Energy efficiency class (A - G): | G                               |
| EPREL-Nr:                        | 1311455                         |

**Scope of delivery:**

- 1 x spotlight
- 1 x filter frame
- 1 x lamp clamping ring
- 1 x user manual