



Features:

Logistic

EUROLITE T-36 Pinspot with Cable, black

Pinspot for PAR-36 6 V/30 W lamp

- At a distance of 4 m there is projected a light circle with a diameter of 30 cm
- Separately capsuled transformator chamber
- Color caps or color foils can be attached in front of the lens
- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- Interesting price levels for purchase of larger quantities
- Low power consumption
- Control via plug and play
- With mounting bracket
- Various versions available
- For application areas such as: Clubs/dancing school; decoration; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation

OMNILUX PAR-36 6.4V/30W G-53 VN5P 200h

PAR-36 lamp

- Harmless for color-foils
- The heat permeates the front-glass continuously
- Dimmable

- Very high color rendering index (CRI)

Technical specifications:

Weight:	14.56 kg
---------	----------

EUROLITE T-36 Pinspot with Cable, black

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 30 W
Protection class:	Protection class I
Suitable lamp:	Max. 6.4 V/30 W PAR-36 G-53 STC
Power connection:	Fixed supply cord with open wires
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 0.9 m
Base:	Wires
Control:	Plug and play
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Metal
Dimensions:	Length: 16 cm Width: 15.5 cm Height: 17 cm
Weight:	1.00 kg
Noise classification:	Class 0 (no noise at all)
Material:	Metal
Diameter mounting holes:	3 x Ø10mm; 1 x Ø8mm
Material:	Metal, 2 mm

OMNILUX PAR-36 6.4V/30W G-53 VNSP 200h

Operating voltage:	6.4 V
Nominal wattage:	30 W
Base:	G-53 STC
Lamp type:	Incandescent lamp; halogen lamp
Lamp specification:	Dimmable
Beam angle:	6°
Color of light:	Warm white WW <3300 K
Color rendering index (CRI):	99 Ra
Lead time:	0.2 s
Construction:	PAR-36
Operating temperature max.:	+40° C
Operating temperature min.:	-20° C

Burning position:	S180 (universal)
Lamp life:	200 h
Luminous flux:	510 lm
Wavelength:	778 nm
Dimensions (LxD):	70x114 mm
Weight:	0.21 kg
Energy efficiency class (A - G):	G
EPREL-Nr:	1015336

Scope of delivery:

1 x spotlight
1 x lamp clamping ring
1 x user manual