# EUROLITE Set Outdoor Bar incl. controller

**Art. No.: 09009214**

GTIN:





## Features:

**EUROLITE LED IP T1000 RGB 10mm 40°**

Brilliant high-power LED RGB outdoor color changer

- Functions: static colors, automatic color change, internal programs, strobe effect, Master/Slave
- Control in stand-alone mode and DMX programming via optional IR remote (necessary for use)
- DMX control via regular DMX controller (occupies 5 channels)
- Ideal LED luminary for outdoor use
- Fixed installation is recommended
- Locking possibility at the mounting bracket
- Perfect in public places and in front of buildings
- The weather-resistant housing also allows operation during bad weather
- Extremely compact housing in an appealing design
- Ready for connection with power cord and safety power plug
- For the usage a DMX cable adapter is necessary
- Available in 2 sizes
- Available in 20° or in 40° versions of the LED beam angle
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free
- Can be operated in 5 CH mode
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

**EUROLITE IR-Remote for LED-Devices**

Addressing and programming via infrared

- Operable up to 10 m
- Functions: programming of RGB dimming, Master/Slave function, DMX mode, DMX addressing as well as internal programs, auto mode, strobe effect with adjustable speed
- Control via IR remote control

## Technical specifications:

| | |
|---|---|
| Weight: | 4.47 kg |

**EUROLITE LED IP T1000 RGB 10mm 40°**

| | |
|---|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 40 W |
| IP classification: | IP65 |
| DMX channels: | 5 |
| Fixtures available for: | Light´J |
| Beam angle (1/2 peak): | 40° |
| Dimensions: | Length: 100 cm<br>Depth: 8 cm<br>Height: 17 cm |
| Number of DMX channels: | 5 |
| Protection grade: | IP65 |
| LED type: | 10 mm |
| LED number: | 240 |
| Beam angle: | 40° |
| Dimensions (L x W x H): | 1000 x 80 x 170 mm |
| Weight: | 5 kg |

**EUROLITE IR-Remote for LED-Devices**

| | |
|---|---|
| Control: | IR remote control |
| Dimensions: | Width: 4.6 cm<br>Depth: 11 cm<br>Height: 0.7 cm |
| Weight: | 0.02 kg |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |

## Scope of delivery:

1 x remote control
1 x battery

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.