



Features:

Logistic

FUTURELIGHT EYE-7 RGBW LED Moving-Head Beam

4in1 moving head beam with 15 W LEDs

- Equipped with 7 x 15 W quadcolor LED with RGBW colors (Osram)
- Compact housing
- Narrow illumination angle
- High PAN/TILT speed
- Supports RDM (Remote Device Management)
- 14, 16 or 22 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity and colors
- Master dimmer
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset

- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller

ROADINGER Flightcase 6x EYE-7 RGBW

Trunk case with castors

- Compartments for 6 units and accessory
- Interior and cover upholstered with foam
- High-quality workmanship with multiplex birch wood, black laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, large steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 large butterfly locks (without locking function)
- 4 hinged, chromium plated case handles
- Castors
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	61.40 kg
---------	----------

FUTURELIGHT EYE-7 RGBW LED Moving-Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100.00 W
Dimensions:	Width: 17.9 cm Depth: 35 cm Height: 24.4 cm
DMX channels:	14/16/22
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED number:	7
LED type:	15 W QCL
Beam angle:	7°
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	244 x 179 x 350 mm
Weight:	6 kg

ROADINGER Flightcase 6x EYE-7 RGBW

Maximum load:	100 kg
---------------	--------

Transport aid:	Castors
Material:	Birch multiplex, 7 mm
Color:	Black, laminated
Dimensions:	Width: 92 cm Depth: 53.5 cm Height: 57.5 cm
Weight:	23 kg
Strength:	7 mm
Outside dimensions (W x D x H):	920 x 535 x 575 mm
Inside dimensions (W x D x H):	880 x 490 x 350 mm
Device compartment (W x D x H):	255 x 245 x 315 mm

Scope of delivery: