

## OMNITRONIC PM-322 DJ mixer

PRO 2+1-channel DJ mixer

Art. No.: 10006816

GTIN: 4026397193459



The article is no longer in our assortment.

### Features:

- 2 input channels, switchable phone/line with 3-way equalizer
- 1 separate DJ mic channel with input sensitivity control (gain), 2-fold tone control (bass, treble) and talkover selector
- Microphone input via 6.3 mm mono jack on the faceplate
- High-quality and super-smooth channel faders
- Super-smooth crossfader replaceable from above
- Headphones output adjustable via Cue Level control
- Additional Cue Split/Cue Mix switch
- Cue Split function: the Cue signal is on the one side of the headphones and the output signal on the other side
- Cue Mix function: the adjustable mix of Cue signal and output signal is on both sides of the headphones
- Mixing of the headphones signal possible via cue mixing fader
- Master out 10-fold LED level displays (L/R)
- Master control
- Rec Out independent from Master level for records with static level

### Logistic

EAN / GTIN: 4026397193459

Weight: 2,50 kg

Length: 0.27 m

Width: 0.13 m

Height: 0.34 m

### Technical specifications:

|                    |                                |
|--------------------|--------------------------------|
| Power consumption: | 4.50 W                         |
| Frequency range:   | 20 - 20000 Hz                  |
| Dimensions:        | Width: 17.8 cm<br>Depth: 27 cm |

|                        |                         |
|------------------------|-------------------------|
|                        | Height: 8.5 cm          |
| Weight:                | 2.05 kg                 |
| Power supply:          | 230 V AC, 50 Hz,        |
|                        | via supplied power unit |
| Inputs:                | 2 phono, 4 line, 1 mic  |
| Minimum input voltage: |                         |
| Microphone:            | 2 mV, 4 kohms           |
| Phono:                 | 3 mV, 50 kohms          |
| Line:                  | 200 mV, 6 kohms         |
| Output voltage:        | 4.5 V peak to peak      |
| Outputs:               | 1 master, 1 rec via RCA |
| Distortion:            | <0.09 %                 |
| S/N ratio:             | 60 dB                   |
| Talkover attenuation:  | -14 dB                  |

### Scope of delivery: