

OMNITRONIC RS-602 Recording Mixer

Compact 6-channel studio and live mixer

Art. No.: 10040050

GTIN: 4026397183238



The article is no longer in our assortment.

Features:

- Low-noise 6-channel mic/line mixer
- 2 mono inputs with XLR sockets, +48V phantom power and balanced line inputs
- 2 stereo inputs with balanced 6.3 mm jack sockets
- Stereo inputs can also be operated mono
- 3-band EQ for all inputs
- Peak LED per mono input
- Aux send per channel for controlling external effectors
- Stereo aux return with balanced 6.3 mm jack sockets
- Separate main mix, booth and headphones outputs
- Tape inputs assignable to master, booth/headphones
- Precise 10-fold stereo LED meter

Logistic

EAN / GTIN: 4026397183238

Weight: 2,90 kg

Length: 0.32 m

Width: 0.30 m

Height: 0.12 m

Technical specifications:

Power consumption:	15.00 W
Dimensions:	Width: 22 cm Depth: 25 cm Height: 5.5 cm
Weight:	2.40 kg
Power supply:	2 x 20 V AC, 50/60 Hz via included power unit
Inputs:	

2 x mono	XLR or balanced 6.3 mm jack
2 x stereo	balanced 6.3 mm jacks
1 x Aux Return:	balanced 6.3 mm jacks
1 x Tape In	stereo RCA
Outputs:	
1 x Master Out	balanced 6.3 mm jacks
1 x Control Room	balanced 6.3 mm jacks
1 x Aux Send:	balanced 6.3 mm jacks
1 x Tape Out	stereo RCA
Frequency range:	
Microphone:	10-60000 Hz, ±3 dB
Mono:	10-60000 Hz, ±3 dB
Stereo:	10-55000 Hz, ±3 dB
Distortion:	0.01 %
S/N ratio:	112 dB
Tone control/channel:	
Treble:	±15 dB at 12 kHz
Middle:	±15 dB at 2.5 kHz
Bass:	±15 dB at 80 Hz
Dimensions (W x D x H):	220 x 250 x 55 mm

Scope of delivery:
