

## OMNITRONIC LRS-1002 Live Recording Mixer

Live recording mixer with 10 inputs

Art. No.: 10040220

GTIN: 4026397449112



### Features:

- 2 mono input channels with gain control, 3-way EQ and pan control
- 2 stereo input channels with 3-way EQ and balance control
- Adjustable stereo aux return input and FX send output
- Inserts for the mono input channels
- Tape input and output
- Separate main mix and control room outputs
- Adjustable headphones output
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level display
- Operation via supplied power unit

### Logistic

EAN / GTIN: 4026397449112

Weight: 1,85 kg

Length: 0.33 m

Width: 0.24 m

Height: 0.09 m

### Technical specifications:

|                    |                                              |
|--------------------|----------------------------------------------|
| Power consumption: | 10.00 W                                      |
| Frequency range:   | 20 - 20000 Hz                                |
| Dimensions:        | Width: 19 cm<br>Depth: 25 cm<br>Height: 5 cm |
| Weight:            | 1.55 kg                                      |
| Power supply:      | 2 x 18.5 V AC, 350 mA<br>via supplied PSU    |

**Inputs/sensitivity:**

|                 |                                       |
|-----------------|---------------------------------------|
| Mic, mono       | 0.5 mV, combined XLR/6.3 mm jack bal. |
| Insert          | 140 mV, 6.3 mm jack unbal.            |
| Line In, stereo | 60 mV, 6.3 mm jack L/R bal.           |
| Aux Return:     | 60 mV, 6.3 mm jack L/R bal.           |
| Tape In         | 400 mV, RCA L/R                       |

**Outputs/level:**

|                       |                                  |
|-----------------------|----------------------------------|
| Main Out:             | 800 mV, 6.3 mm jack L/R unbal.   |
| Control Room          | max. 3 V, 6.3 mm jack L/R unbal. |
| FX Send               | max. 10 V, 6.3 mm jack unbal.    |
| Tape Out              | 60 mV, RCA L/R                   |
| Headphones            | 6.3 mm jack unbal.               |
| Headphones impedance: | >8 ohms                          |
| Distortion:           | <0.04 %                          |
| S/N ratio:            | 91 dB                            |

**Tone control/channel:**

|                         |                   |
|-------------------------|-------------------|
| Treble:                 | ±15 dB at 12 kHz  |
| Middle:                 | ±15 dB at 2.5 kHz |
| Bass:                   | ±15 dB at 80 Hz   |
| Dimensions (W x D x H): | 190 x 250 x 50 mm |

**Scope of delivery:**