

## OMNITRONIC LRS-1402ST Live Recording Mixer

Live recording mixer with 14 inputs

Art. No.: 10040229

GTIN: 4026397449143



**The article is no longer in our assortment.**

### Features:

- 4 mono input channels with gain control, 3-way EQ, low cut and pan control
- 4 stereo input channels with balance control
- Adjustable FX send output
- Inserts for the mono input channels
- Tape input and output
- Separate main mix and control room outputs
- Adjustable headphones output
- Master fader
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level display
- Operation via supplied power unit

### Logistic

EAN / GTIN: 4026397449143

Weight: 2,20 kg

Length: 0.33 m

Width: 0.29 m

Height: 0.09 m

### Technical specifications:

|                    |                                                  |
|--------------------|--------------------------------------------------|
| Power consumption: | 10.00 W                                          |
| Frequency range:   | 20 - 20000 Hz                                    |
| S/N ratio:         | >94 dB                                           |
| Dimensions:        | Width: 22.5 cm<br>Depth: 24.5 cm<br>Height: 5 cm |
| Weight:            | 1.80 kg                                          |
| Power supply:      | 2 x 18.5 V AC, 350 mA                            |

via supplied PSU

Inputs/sensitivity:

|                 |                                       |
|-----------------|---------------------------------------|
| Mic, mono       | 0.5 mV, combined XLR/6.3 mm jack bal. |
| Insert          | 140 mV, 6.3 mm jack unbal.            |
| Line In, stereo | 38 mV/150 mV, 6.3 mm jack L/R bal.    |
| Tape In         | 400 mV, RCA L/R                       |

Outputs/level:

|              |                                  |
|--------------|----------------------------------|
| Main Out:    | 800 mV, 6.3 mm jack L/R unbal.   |
| Control Room | max. 3 V, 6.3 mm jack L/R unbal. |
| FX Send      | max. 10 V, 6.3 mm jack unbal.    |
| Tape Out     | 60 mV, RCA L/R                   |

|            |                    |
|------------|--------------------|
| Headphones | 6.3 mm jack unbal. |
|------------|--------------------|

|                       |         |
|-----------------------|---------|
| Headphones impedance: | >8 ohms |
|-----------------------|---------|

|             |         |
|-------------|---------|
| Distortion: | <0.04 % |
|-------------|---------|

Tone control/channel:

|         |                  |
|---------|------------------|
| Treble: | ±15 dB at 12 kHz |
|---------|------------------|

|         |                   |
|---------|-------------------|
| Middle: | ±15 dB at 2.5 kHz |
|---------|-------------------|

|       |                 |
|-------|-----------------|
| Bass: | ±15 dB at 80 Hz |
|-------|-----------------|

|                         |                   |
|-------------------------|-------------------|
| Dimensions (W x D x H): | 225 x 245 x 50 mm |
|-------------------------|-------------------|

Scope of delivery: