

OMNITRONIC MRS-502USB Recording Mixer

Mini audio mixer with USB interface

Art. No.: 10040270

GTIN: 4026397513875



Features:

- Built-in USB audio interface allows recordings and playback of digital audio files with a computer (PC and Mac)
 - Full duplex USB port allows simultaneous recording and playback
 - 1 mono input channel with gain control, 2-band EQ and pan control, clip LED
 - 1 stereo input channel with level control, 2-band EQ and balance control
 - Tape input and output
 - 3.5 mm stereo master output
 - Adjustable headphones output
 - +20 V phantom power, permanent
 - Clip LED
 - Rugged, compact metal housing
- mixer**
- Desktop console housing

Logistic

EAN / GTIN: 4026397513875

Weight: 0,65 kg

Length: 0.23 m

Width: 0.17 m

Heigh: 0.05 m

Technical specifications:

Power consumption:	2.50 W
Frequency range:	20 - 20000 Hz
S/N ratio:	>81 dB
THD:	<0.05 % at 1 kHz
Phantom power:	20 V DC
Control elements:	Power switch, source selector

Status LED:	Clip, power
Connections:	Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x stereo RCA 0.15 V Input: line via 1 x stereo RCA 0.42 V Output: line via 1 x stereo RCA 2 V Output: line via 1 x 3.5 mm jack (stereo) mounting version 6 V Output: headphones via 1 x 3.5 mm jack (stereo) mounting version 2 V
Channels:	Microphone channel: 1 x mono via XLR or jack, channel control via rotary dial, 2-band tone control EQ 80Hz/12kHz, gain control, panoramacontrol Input channel: 1 x stereo with line-USB switch via RCA or USB, channel control via rotary dial, 2-band tone control EQ 80Hz/12kHz, balancecontrol Master output: 1 x stereo via jack, channel control via rotary dial Headphones output: 1 x stereo via jack, channel control via rotary dial
USB port:	USB 2.0, type B
Dimensions:	Width: 10.3 cm Depth: 14.8 cm Height: 4.7 cm
Weight:	0.53 kg
Power supply:	5V 500 mA
Power connection:	Mains input via USB, type B power supply cord with AC adapter (provided)
Housing color:	Black
Material:	Metal
Housing design:	Desktop console housing
Power supply:	100-240 V AC, 50/60 Hz

Scope of delivery:

1 x mixer
 1 x external mains adapter
 1 x USB cable
 1 x user manual