

OMNITRONIC LH-060 PRO Dual DI Box passive

Passive 2-channel DI box/splitter, silver

Art. No.: 10355060

GTIN: 4026397194890



Features:

- 2 high-impedance signal inputs via combo connectors (XLR/6.3 mm jack)
- 2 low-impedance XLR outputs
- Converts 2 separate unbalanced line inputs (e.g. CD player, instruments) into 2 balanced XLR outputs, for connecting a mixer
- Switchable to split mode (input 2 routes the signal to both outputs)
- Switchable input attenuation: 0 dB, -20 dB, -40 dB
- Cables can be routed under the housing
- For application areas such as: Installation; mobile use; mobile djs / entertainer

Logistic

EAN / GTIN: 4026397194890

Weight: 0,82 kg

Length: 0.23 m

Width: 0.16 m

Height: 0.09 m

Technical specifications:

Frequency range:	15 - 30000 Hz
Impedance:	Input: 50 kOhm Output: 600 Ohm
Input attenuation:	0 dB, -20 dB, -40 dB; switchable
Housing color:	Silver
Control elements:	Groundlift selector
Connections:	Input: 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 2 x 3-pin XLR
Max. level:	Output: +6 dBu

Dimensions:	Width: 15 cm
	Depth: 13 cm
	Height: 6 cm
Weight:	0.65 kg

Scope of delivery:

1 x device
1 x user manual