

OMNITRONIC LH-075 Tube mic preamplifier

1-channel vacuum tube mic preamplifier with integrated limiter

Art. No.: 10355075

GTIN: 4026397194951



The article is no longer in our assortment.

Features:

- 12AX7 vacuum tube adds warm sound to digital recorders and sound cards
- Signal inputs and outputs via balanced XLR connectors and 6.3 mm jacks
- Limiter can be switched on
- +48 V phantom power can be switched on
- Microphone phase can be switched
- Input attenuation can be switched on (+20 dB)
- Precise 5-digit LED meter with Peak LED for output level
- Adjustable gain
- Adjustable output level
- Modern convex housing design
- Full rubber housing corners for safe operation
- Cables can be routed under the housing
- Operation via supplied power unit

Logistic

EAN / GTIN: 4026397194951

Weight: 1,40 kg

Length: 0.23 m

Width: 0.16 m

Height: 0.10 m

Technical specifications:

Power consumption:	15.00 W
Frequency range:	10 - 20000 Hz
Dimensions:	Width: 15 cm Depth: 6 cm Height: 13 cm
Weight:	1.2 kg

Power supply:	9 V AC, 1500 mA
Input impedance:	2 kohms (XLR), 840 kohms, 6.3 mm jack (1/4")
Output impedance:	600 ohms (XLR), 300 ohms, 6.3 mm jack (1/4")
Maximum output level:	28 dBu (XLR), 22 dBu, 6.3 mm jack (1/4")
Maximum input level:	14 dBu (XLR), 22 dBu, 6.3 mm jack (1/4")
Dynamic range:	>100 dB
Phantom power:	+48 V
Input connectors:	XLR and jack mounting sockets
Output connectors:	XLR and jack mounting plugs
THD:	0.1 %

Scope of delivery:
