

OMNITRONIC XO-34 Active crossover

High-quality stereo crossover

Art. No.: 10355635

GTIN: 4026397233308



Features:

- 2-way/3-way stereo or 4-way mono operation possible
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency 450 Hz - 9 kHz switchable to 45 - 900 Hz
- Individual output level controls for all bands
- Individual output mutes for easy band adjustment
- Phase invert control
- Low Cut switch
- XLR in and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Logistic

EAN / GTIN: 4026397233308

Weight: 2,70 kg

Length: 0.54 m

Width: 0.20 m

Height: 0.08 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 10.00 W

Dimensions: Width: 48.3 cm
Depth: 14.7 cm
Height: 4.45 cm

Weight: 2.25 kg

Slope: 24 dB / octave

Operation modes: 2/3-way stereo or 4-way mono

Input:	Mono/stereo
Input impedance:	10/20 kohms (unb./bal.)
Output:	Mono/stereo
Output impedance:	300/150 kohms (unb./bal.)
In/Out connectors:	XLR
S/N ratio:	>100 dB
Xover frequency range:	45-9000 Hz
THD:	0.05%
Crosstalk:	>80 dB, -3 dB
Input gain:	-- to +6 dB
Output gain:	-- to +12 dB
Low Cut:	30 Hz, -3 dB
Dimensions (W x D x H):	483 x 147 x 46 mm

Scope of delivery: