

OMNITRONIC ISO-23FX DJ Isolator

3-band frequency isolator with kill cut and FX loop for DJs

Art. No.: 10355902

GTIN: 4026397423457



The article is no longer in our assortment.

Features:

- 3-band frequency isolator with dedicated boost and kill cut for DJs
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Vintage ALPS potentiometers (Blue Velvet RK27)
- High-grade components ensure long life and excellent sound quality
- 1-channel stereo version
- Control range: kill to +6 dB
- Lows: 20 Hz - 300 Hz
- Mids: 300 Hz - 4 kHz
- Highs: 4 kHz - 20 kHz
- Bypass switch
- FX send/return for external FX unit
- FX dry/wet adjustment
- Stereo RCA connectors
- Rack installation, 1 U
- (19") 48.3 cm rack installation 1 U

Logistic

EAN / GTIN: 4026397423457

Weight: 3,45 kg

Length: 0.54 m

Width: 0.26 m

Height: 0.08 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	10.00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Frequency range:	20 - 20000 Hz
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48.3 cm Depth: 20 cm Height: 4.45 cm
Weight:	2.90 kg
Connectors:	stereo RCA
Maximum input level:	+22 dBu
Maximum ouput level:	+22 dBu
Control range:	-~ to +6 dB
Lows:	20 Hz to 300 Hz
Mids:	300 Hz to 4 kHz
Highs:	4 kHz to 20 kHz

Scope of delivery: