

# OMNITRONIC ISO-23FX DJ Isolator

3-band frequency isolator with kill cut and FX loop for DJs

Art. No.: 10355902

GTIN: 4026397423457



## Features:

- 3-band frequency isolator with dedicated boost and kill cut for DJs
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Vintage ALPS potentiometers (Blue Velvet RK27)
- High-grade components ensure long life and excellent sound quality
- 1-channel stereo version
- Control range: kill to +6 dB
- Lows: 20 Hz - 300 Hz
- Mids: 300 Hz - 4 kHz
- Highs: 4 kHz - 20 kHz
- Bypass switch
- FX send/return for external FX unit
- FX dry/wet adjustment
- Stereo RCA connectors
- Rack installation, 1 U
- (19") 48.3 cm rack installation 1 U

## Logistic

EAN / GTIN: 4026397423457  
Weight: 3,45 kg  
Length: 0.54 m  
Width: 0.26 m  
Heigh: 0.08 m

## Technical specifications:

|                    |                                                                                                  |
|--------------------|--------------------------------------------------------------------------------------------------|
| Power supply:      | 230 V AC, 50 Hz                                                                                  |
| Power consumption: | 10.00 W                                                                                          |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| Frequency range:      | 20 - 20000 Hz                                     |
| Housing design:       | (19") 48.3 cm rack installation 1 U               |
| Dimensions:           | Width: 48.3 cm<br>Depth: 20 cm<br>Height: 4.45 cm |
| Weight:               | 2.90 kg                                           |
| Connectors:           | stereo RCA                                        |
| Maximum input level:  | +22 dBu                                           |
| Maximum output level: | +22 dBu                                           |
| Control range:        | ~- to +6 dB                                       |
| Lows:                 | 20 Hz to 300 Hz                                   |
| Mids:                 | 300 Hz to 4 kHz                                   |
| Highs:                | 4 kHz to 20 kHz                                   |

### **Scope of delivery:**