

OMNITRONIC ISO-23 MK2 DJ Isolator

3-band frequency isolator with kill cut and bypass for DJs

Art. No.: 10355903

GTIN: 4026397655223



List price: 236.81 €

incl. 19% VAT.

Description:

3-band frequency isolator with vintage rotary knobs for DJs

With the Omnitronic ISO-23 MK2 frequency isolator DJs get an effective tool for creative sound shaping in the club or studio. Using high-grade, long-life ALPS RK27 potentiometers, the rack-mounted isolator has excellent sound characteristics.

The large, smooth rotary knobs enable DJs to radically boost or cut low, mid or high frequencies, making it easy to create instrumental or a cappella versions. The isolator provides XLR and RCA connectors and features a bypass switch for bridging.

Features:

- 3-band frequency isolator with dedicated boost and kill cut for DJs
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Classic ALPS potentiometers (Blue Velvet RK27)
- 1-channel stereo version
- Lows: 20 Hz - 300 Hz
- Mids: 300 Hz - 4 kHz
- Highs: 4 kHz - 20 kHz
- Bypass switch
- Balanced and unbalanced inputs/outputs (XLR/RCA)
- (19") 48.3 cm rack installation 1 U
- For application areas such as: Clubs/dancing school; mobile use; mobile djs / entertainer; homerecording and studios

Logistic

EAN / GTIN: 4026397655223

Weight: 2,44 kg

Length: 0.54 m

Width: 0.26 m

Height: 0.10 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	12 W
Protection class:	Protection class I
Isolators:	Master Gain:- ? bis +9 Low/mid 300 Hz, 18db/oct , Butterworth Mid/high 4000 Hz, 18db/oct , Butterworth
Connections:	Input: line via 2 x 3-pin XLR Input: line via 2 x RCA (F) mounting version Output: line via 2 x 3-pin XLR Output: line via 2 x RCA (F) mounting version
Max. level:	Input: +22 dBu
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48.3 cm Depth: 14.5 cm Height: 4.45 cm
Weight:	2.04 kg

Scope of delivery:

- 1 x device
- 1 x power cord
- 4 x foot