

OMNITRONIC TRM-402 4-channel Rotary Mixer

4-channel rotary mixer with 3-band frequency isolator for DJs

Art. No.: 10355930

GTIN: 4026397659948



List price: 534.31 €

incl. 19% VAT.

Features:

- Classic rotary mixer with 4 input channels and integrated 3-band frequency isolator for DJs
- Gain control, 2-way equalizer (highs/low) and phono/line switching per channel
- Dedicated boost and kill cut
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Classic ALPS potentiometers (Blue Velvet RK27)
- High-grade components ensure long life and excellent sound quality
- DJ microphone input with separate level control
- Prefader listening to input channels and the master output via adjustable headphones output, with cue mix/split function
- 12-digit stereo LED level meter and master level control
- Booth output with separate level control
- Dual inputs for DJ microphone and headphones on the top and front panel
- Outputs: master and booth (XLR/RCA L/R), record (stereo RCA)
- Desktop console housing
- For application areas such as: Clubs/dancing school; mobile use; mobile djs / entertainer; homerecording and studios

Logistic

EAN / GTIN: 4026397659948

Weight: 4,60 kg

Length: 0.42 m

Width: 0.29 m

Height: 0.14 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 7.2 W

Protection class: Protection class I

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20000 Hz microphone 20 - 20000 Hz line 40 - 18000 Hz phono
S/N ratio:	>77 dB phono >80 dB microphone >85 dB line
THD:	Line <0.03 % at 1 kHz Phono <0.1 % at 1 kHz
Gain:	Microphone 44 dB Line 20 dB Phono 60 dB to +75 dB
Isolators:	Master Gain: - ∞ bis +9 Low/mid 300 Hz, 18db/oct , Butterworth Mid/high 4000 Hz, 18db/oct , Butterworth
Control elements:	Power switch, source selector, cue mix split function, tone control
Status LED:	Power, master level meter, channel source, CUE, microphone
Connections:	Input: line via 4 x stereo RCA Input: line/phono via 4 x stereo RCA Input: microphone via 2 x 3-pin XLR Output: headphones via 2 x 6.3 mm jack socket (stereo) mounting version Output: headphones via 2 x 3.5 mm jack (stereo) mounting version Output: rec. via 1 x stereo RCA Output: booth via 2 x 3-pin XLR Output: booth via 1 x stereo RCA Output: master via 2 x 3-pin XLR Output: master via 1 x stereo RCA
Channels:	Input channel: 4 x stereo with line-line/phono switch via RCA, channel control via rotary, 2-band tone control EQ, gain control, phono gain rotary, CUE switch, source selector Microphone channel: 1 x mono via XLR, channel control via rotary dial, ON AIR switch Booth output: 1 x stereo via XLR or RCA, channel control via rotary dial Master output: 1 x stereo via XLR or RCA, channel control via rotary dial Headphones output: 1 x stereo via jack, channel control via rotary dial, cue mix split function
Max. level:	Output: +22 dBu
Material:	Metal
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 33 cm Depth: 24.7 cm Height: 10.7 cm
Weight:	4.05 kg

Scope of delivery:

1 x device
1 x power cord
1 x user manual