

OMNITRONIC DXO-26E Digital Controller

Digital Speaker Management System with 2 inputs and 6 outputs, incl. software

Art. No.: 10356341

GTIN: 4026397651119



The article is no longer in our assortment.

Features:

- Flexible routing configurations for all standard mono and stereo output operating modes
- 2 analog inputs and 6 analog outputs (XLR)
- Active crossover with Bessel, Butterworth and Linkwitz-Riley filter with slopes up to 24 dB/octave
- Up to 30 user presets storable in the device via software
- Input sensitivity digitally adjustable
- Inputs and outputs with 4-digit LED level meter as well as clip and limit LED indicator
- Mute switch with LED indicator per output
- 7-band parametric EQ per output
- Up to 7 ms signal delay adjustable for the outputs
- Output limiter with adjustable limits and automatic attack and release settings as overload protection for your amplifying system
- Switchable phase
- Lock function for prevents undesired changes to settings
- Sample rate: 67 kHz
- (19") 48.3 cm rack installation 1 U
- Digital signal processor
- Monochrome LCD display
- The device can be connected via USB to the PC in connection with DXO Software
firmware can be updated
- Compatible with Win XP, Win Vista, Win 7, Win 10, OS X 10.5 or better
- For application areas such as: Clubs/dancing school; installation; mobile djs / entertainer; restaurants, bars and hotels; rental

Logistic

EAN / GTIN: 4026397651119

Weight: 2,08 kg

Length: 0.53 m

Width: 0.26 m

Height: 0.08 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 6V 800 mA
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Frequency range:	10 - 30000 Hz
THD:	<0.005 % at 1 kHz
DSP:	Digital signal processor
Impedance:	Input: 10 kOhm Output: 50 Ohm
Gain:	Output: -50 dB to +12 dB
Filter:	Linkwitz-Riley; Butterworth; Bessel; 6db/oct; 12db/oct; 18db/oct; 24db/oct
Delay:	0 - 5 ms
Dynamic range:	Input: 114 dB Output: 110 dB
Sample rate:	67 kHz
Display type:	Monochrome LCD display
Control elements:	Mute control, encoder, navigation keys
Status LED:	Limit, clip, level meter, Mute
Connections:	Input: line via 2 x 3-pin XLR Output: line via 6 x 3-pin XLR
Crossover frequency:	20-20000 Hz
Max. level:	Input: +22 dBu Output: +9 dBu
USB port:	Type B
Color:	Black
PC connect:	DXO Software via USB, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48.3 cm Depth: 12.8 cm Height: 4.45 cm
Weight:	1.77 kg
Operating system:	Win XP, Win Vista, Win 7, Win 10, OS X 10.5 or better

Scope of delivery:

1 x controller
1 x user manual
1 x USB cable
1 x external mains adapter
4 x foot
1 x CD