

OMNITRONIC DFE-212 Feedback exterminator

Feedback-free weekends guaranteed

Art. No.: 10356510

GTIN: 4026397177787



The article is no longer in our assortment.

Features:

- The feedback exterminator avoids quickly and effectively any occurring feedbacks in your amplifying system
- Connection via balanced XLR sockets or jacks
- 12 automatically controlled feedback frequencies per channel
- 3 different modes: Single, Auto, Manual
- MIDI-control possible

Logistic

EAN / GTIN: 4026397177787

Weight: 2,85 kg

Length: 0.52 m

Width: 0.25 m

Height: 0.09 m

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	10.00 W
Dimensions:	Width: 48.3 cm Depth: 15.2 cm Height: 4.45 cm
Weight:	2.15 kg
Inputs:	XLR or balanced 6.3 mm jack
Nominal Operating Level:	-20 dB to +4 dB
Max. input level:	+16 dB at +4 dB nominal level, +2 dB at -20 dB nominal level
Input impedance:	40 ohms balanced, 20 ohms unbalanced

Outputs:	XLR or balanced 6.3 mm jack
Max. output level:	+16 dB at +4 dB nominal level, +2 dB at -20 dB nominal level
Output impedance:	66 ohms balanced, 33 ohms unbalanced
Frequency range:	20-20000 Hz
Distortion:	0.06 %
S/N-ratio:	98 dB, 20-20000 Hz
Crosstalk:	-95 dB, 20-20000 Hz
MIDI-Interface:	5-pin DIN-socket IN/OUT/THRU
Converters:	24-bit Sigma-Delta, 64/128-times oversampling
Sampling rate:	48 kHz
Dimensions (W x D x H):	482 x 152 x 45 mm

Scope of delivery: