

## OMNITRONIC XDA-2402 Class D Amplifier

Class D stereo PA amplifier with SMPS, 2 x 1200 W RMS (4 ohms), 2 x 880 W RMS (8 ohms)

Art. No.: 10451636

GTIN: 4026397580150



**List price: 653.31 €**

incl. 19% VAT.

### Features:

- Stereo PA amplifier with class D circuitry
- Low weight and height due to integrated switch mode power supply
- 2 level controls
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs
- Speaker outputs via lockable Speaker plugs
- (19") 48.3 cm rack installation 1 U
- The device is cooled by cooling fan
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; rental; sports centres/gyms

### Logistic

EAN / GTIN: 4026397580150

Weight: 7,75 kg

Length: 0.59 m

Width: 0.47 m

Height: 0.07 m

### Technical specifications:

|                    |                                                                                                 |
|--------------------|-------------------------------------------------------------------------------------------------|
| Power supply:      | 230 V AC, 50 Hz                                                                                 |
| Power consumption: | 465 W 1/8 power                                                                                 |
| Protection class:  | Protection class I                                                                              |
| Output power:      | 2 x 1200 W RMS (4 ohms)<br>2 x 880 W RMS (8 ohms)                                               |
| Power connection:  | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided) |
| Frequency range:   | 30 - 20000 Hz                                                                                   |
| S/N ratio:         | >100 dB                                                                                         |

|                    |                                                                                                                      |
|--------------------|----------------------------------------------------------------------------------------------------------------------|
| THD:               | <0.02 % at 1 kHz                                                                                                     |
| Cooling:           | Cooling fan                                                                                                          |
| Impedance:         | Input: 20 kOhm , bal.<br>Input: 10 kOhm , unbal.                                                                     |
| Housing color:     | Black matte                                                                                                          |
| Circuitry:         | Class D                                                                                                              |
| Control elements:  | Power switch, level control per channel, groundlift selector                                                         |
| Controls:          | Short-circuit; overheat; DC voltage; power on/off transients; softstart; power on/off transient; limiter             |
| Status LED:        | Power, signal, limit, protect                                                                                        |
| Connections:       | Input: line via 2 x 3-pin XLR<br>Link: line via 2 x 3-pin XLR<br>Output: speaker via 2 x speaker built-in socket (F) |
| Input sensitivity: | 1.25 V                                                                                                               |
| Housing design:    | (19") 48.3 cm rack installation 1 U                                                                                  |
| Dimensions:        | Width: 48.3 cm<br>Depth: 35.5 cm<br>Height: 4.45 cm                                                                  |
| Weight:            | 6.40 kg                                                                                                              |

**Scope of delivery:**

- 1 x amplifier
- 1 x user manual
- 1 x power cord