



DDA-1700 Amplifier

Class D stereo PA amplifier with SMPS, 2 x 850 W RMS (4 ohms), 2 x 500 W RMS (8 ohms)

Art. No.: 10451684

GTIN: 4026397614459



DDA-1700 Amplifier

Class D stereo PA amplifier with SMPS, 2 x 850 W RMS (4 ohms), 2 x 500 W RMS (8 ohms)

Art. No.: 10451684

GTIN: 4026397614459

Features:

- Stereo PA amplifier with class D circuitry
- Low weight and height due to integrated switch mode power supply
- Reliable power amp with high impulse stability for a wide range of applications (e.g. compact PAs, multi-way PAs, concerts)
- Limiter and speaker switch-on delay
- 3 operating modes can be selected (stereo, parallel or bridged)
- 2 calibrated level controls for precise level adjustment
- Input sensitivity adjustable
- LED VU meter and LEDs for activated protective circuit (protect) and overload (clip) per channel
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs
- Speaker outputs via lockable Speaker plugs
- Rugged steel chassis with aluminum front panel
- (19") 48.3 cm rack installation 2 U
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan