

## OMNITRONIC DMS-1150 MP3 workstation

MP3 Scratch workstation

Art. No.: 10602426

GTIN: 4026397261578



### Features:

- For MP3 and Audio CDs, CD-Rs, CD-RWs
- MP3 compatible with ID3 tag support
- 9 DSP sound effects - Scratch, Skid, Filter, Phase, Flanger, Echo, Pan, Trans, Reverse
- Time and Ratio parameters individually adjustable
- Beat Sync function: all effects can be adjusted in accordance with the track speed
- Real time scratch-function without delay and time limit
- Automatic and manual beat counter
- Cue function with 4 cue point hotkeys
- Sampler unit with 4 x 5 seconds sampler time
- All cue points and adjusted sample parameters can be memorized and recalled from up to 500 CDs
- Seamless Loop and Re-loop function
- Single/Continuous mode
- 10 seconds Anti-Shock
- 1 bit technology (8-fold) instant start
- Pitch adjustment  $\pm 4\%$ ,  $\pm 8\%$ ,  $\pm 16\%$ ,  $\pm 100\%$
- Pitch Bend buttons
- Faderstart function
- Main Tempo function
- Framewise search and cueing via Search buttons and Scratch wheel
- Digital output via RCA
- LCD switchable from track remain time to total remain time to track playback time
- Front-loading CD slot for fast and easy CD exchange

### Logistic

EAN / GTIN: 4026397261578

Weight: 4,00 kg

Length: 0.42 m

Width: 0.35 m

Height: 0.16 m

## Technical specifications:

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| Power supply:       | 115/230 V AC, 50/60 Hz                              |
| Power consumption:  | 17.00 W                                             |
| Dimensions:         | Width: 34.8 cm<br>Depth: 24.6 cm<br>Height: 10.6 cm |
| Weight:             | 3.50 kg                                             |
| Type:               | Compact Disc/ MP3 player                            |
| Available disc:     | Standard CDs (8 and 12 cm)                          |
| Quantisation:       | D/A converter: 1 bit                                |
| Sampler frequency:  | 44.1 kHz                                            |
| Frame accuracy:     | 1/75 sec                                            |
| Pitch adjustment:   | ±4 %, ±8 %, ±16 % or 100 %                          |
| Display:            | Remaining track time and track playback time        |
| Distortion:         | 0.01 %, 1 kHz                                       |
| S/N ratio:          | 90 dB                                               |
| Channel separation: | 85 dB                                               |
| Frequency range:    | 20-20000 Hz, ±1 dB                                  |
| Audio output:       | unbalanced via RCA                                  |
| Output level:       | 1 Vrms, ±1 dB                                       |
| Digital output:     | unbalanced via RCA, 44.1 kHz stable                 |
| Dimensions:         | 348 x 246 x 106 mm                                  |

## Scope of delivery: