

OMNITRONIC C-50A active black 2x

Active 2-way speaker pair with mount, 5" woofers and 50 W RMS

Art. No.: 11036716

GTIN: 4026397356274



Features:

- Dedicated PA speaker system for fixed installations
- 2-way system with 13 cm woofer (5") and 2.5 cm dome tweeter (1")
- 2-way tone control and level control
- Signal input and output via balanced XLR connectors
- Trapezoidal cabinet for corner installation
- With mounting bracket
- Black metal grille
- Scratchproof and shockproof
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Logistic

EAN / GTIN: 4026397356274

Weight: 6,80 kg

Length: 0.38 m

Width: 0.21 m

Heigh: 0.28 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Power:	Program: 80W Rated: 50W RMS
Frequency range:	50 - 20000 Hz

Sensitivity:	89 dB (1W/1m)
Attachment system:	Mounting bracket
Control elements:	Level control, tone control, power switch
Status LED:	Power
Connections:	Input: line via 1 x 3-pin XLR (F) mounting version Output: 1 x 3-pin XLR (M) mounting version
Speaker:	1 x woofer 5" Basket material: steel Conematerial: cardboard/paper 1 x tweeter 1"
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black, scratchproof and shockproof
Dimensions:	Width: 18 cm Depth: 16.6 cm Height: 23 cm
Weight:	6.30 kg

Scope of delivery:

2 x compact cabinet speaker
 1 x user manual
 2 x power cord
 8 x screw
 8 x washer