OMNITRONIC EG-40A, active,white/set

Active design speaker pair

Art. No.: 11036866

GTIN: 4026397325188

Features:

- High-quality sound, capable of high volumes due to 2-way system
- 2 x 10 cm woofer (2 x 4") and 2.5 cm tweeter (1")
- 2-way tone control and level control
- Signal input and output via balanced XLR connectors
- Oval-shaped design cabinet with bass-reflex system
- White or black plastic housing (ABS) with metal grille
- Packed as a pair (2 pieces)
- Delivery includes mounting bracket (adjustable at will) for ceiling or wall installation
- Ideal for decentral sound-surroundings in bars, lounges, shops, etc.

Logistic

EAN / GTIN: 4026397325188
Weight: 8,40 kg
Length: 0.40 m
Width: 0.39 m
Heigth: 0.30 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	70.00 W
Frequency range:	60 - 20000 Hz
Dimensions:	Width: 16 cm Depth: 23 cm Height: 32.2 cm
Weight:	7.10 kg
Rated power:	30 W RMS
Program power:	50 W

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Components:	2 x 10 cm woofer (2 x 4"), 2.5 cm horn (1")
Connection:	3-pin XLR
Maximum SPL:	90 dB
Impedance:	4 ohms
Dimensions (H x W x D):	322 x 128 x 230 mm

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.