

OMNITRONIC OD-5A Wall Speaker active white 2x

Active 2-way speaker pair with mount, 5" woofers and 35 W RMS

Art. No.: 11036923

GTIN: 4026397543636



The article is no longer in our assortment.

Features:

- Dedicated PA speaker systems for fixed installations
- 2-way system with 13.5 cm woofer (5.25") and dome tweeter, magnetic shielding
- Class D circuitry: optimum sound and power at low weight and compact dimensions
- Separate controls for volume, high and low frequencies
- Each speaker system is equipped with an unbalanced RCA input and balanced spring terminals
- Attractive plastic cabinet with metal grille
- Panning and tilting mounting bracket allows ceiling or wall installation in most varying angles
- Packed as a pair
- For indoor PA applications
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles

Logistic

EAN / GTIN: 4026397543636

Weight: 6,70 kg

Length: 0.42 m

Width: 0.20 m

Height: 0.28 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with Euro plug (provided)
Power:	Program: 75W Rated: 35W RMS
Frequency range:	80 - 20000 Hz
Sensitivity:	89 dB
Max. SPL:	93 dB

Dispersion angle:	170° x 170°
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Circuitry:	Class D
Connections:	Line via screw plug-in terminal Line via 1 x RCA (F) mounting version
Speaker:	1 x woofer 5" 1 x horn 0.5"
Color:	White
Dimensions:	Width: 16.3 cm Depth: 16 cm Height: 25.5 cm
Weight:	6.25 kg

Scope of delivery: