

## OMNITRONIC OD-8T Wall Speaker 100V black 2x

Weather-proof wall speaker pair (IP65) with 8" woofers and 60 W RMS

Art. No.: 11036932

GTIN: 4026397649116



**List price: 267.75 €**

incl. 19% VAT.

### Description:

Weatherproof wall speaker pair

The OD-8T 100 V sound reinforcement speakers with excellent sound quality are ideal for indoor and outdoor use.

The weatherproof 2-way system in a plastic housing is equipped with a 20 cm woofer, a 2.5 cm dome tweeter with silk membrane and a 100 V transformer with 4 power taps.

The swivel and tilt mounting bracket allows easy wall and ceiling mounting at any angle.

### Features:

- 2-way system with 20 cm woofer (8") and 2.5 cm silk dome tweeter (1")
- Durable plastic cabinet with metal grille and cover for the connectors
- Power selector switch with 8 ohms operating position
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Black aluminum grille
- Suitable for outdoor use IP65
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

### Technical specifications:

IP classification:

IP65

### Logistic

EAN / GTIN: 4026397649116

Weight: 11,20 kg

Length: 0.60 m

Width: 0.29 m

Height: 0.41 m

|                    |                                                                                              |
|--------------------|----------------------------------------------------------------------------------------------|
| Power:             | Program: 120W (8 ohms)<br>Rated: 60W RMS (8 ohms)<br>50W (100V PA)                           |
| Frequency range:   | 30 - 20000 Hz                                                                                |
| Sensitivity:       | 91 dB                                                                                        |
| Max. SPL:          | 110 dB (100V PA); 111 dB (8 ohms)                                                            |
| Dispersion angle:  | 170° x 170°                                                                                  |
| Impedance:         | Public address systems 100V; 8 ohms                                                          |
| Attachment system: | Panning and tilting mounting bracket for ceiling or wall installation in most varying angles |
| Power tapping:     | 6.25W; 12.5W; 25W; 50W RMS via selector switch switchable                                    |
| Control elements:  | Level control                                                                                |
| Connections:       | Input: speaker via spring terminal                                                           |
| Speaker:           | 1 x woofer 8"<br>1 x dome tweeter 1"                                                         |
| Type of speaker:   | Compact cabinet speaker; on ceiling/on wall speaker                                          |
| Color:             | Black                                                                                        |
| Dimensions:        | Width: 24 cm<br>Depth: 24.5 cm<br>Height: 38 cm                                              |
| Weight:            | 10.30 kg                                                                                     |

### Scope of delivery:

2 x compact cabinet speaker  
2 x mounting bracket  
4 x knurled screw  
1 x user manual