

OMNITRONIC ODX-212T Installation Speaker 100V light grey

Weather-proof 12" wall speaker (IP56) with mount, 300 W RMS

Art. No.: 11036964

GTIN: 4026397647662



Description:

Weatherproof 12" wall speaker with mount

The ODX-212T 100 V sound reinforcement box by OMNITRONIC offers excellent sound and is ideally suited for outdoor use with its protection class IP56.

The 2-way coaxial system is equipped with a 30 cm woofer and a 2.5 cm tweeter and a 100 V transformer with 3 power taps. In addition, the wall-mounted speaker has a power switch with an 8-ohm operating setting.

The weatherproof, white plastic housing with the swivel mounting bracket can be mounted at variable angles.

Features:

- 2-way coaxial system with 30 cm woofer (12") and 2.5 cm tweeter (1")
- Durable plastic cabinet with metal grille
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- Suitable for outdoor use IP56
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall

Technical specifications:

IP classification: IP56

Logistic

EAN / GTIN: 4026397647662

Weight: 21,85 kg

Length: 0.47 m

Width: 0.45 m

Height: 0.48 m

Power:	Program: 600W Rated: 300W RMS
Frequency range:	55 - 18000 Hz
Sensitivity:	98 dB (1W/1m)
Max. SPL:	122 dB
Dispersion angle:	80° x 80°
Impedance:	8 ohms; public address systems 100V
Attachment system:	Mounting bracket
Power tapping:	50W; 100W; 200W RMS via selector switch switchable
Connections:	Input: speaker via screw terminal
Crossover frequency:	2200 Hz
Speaker:	1 x woofer 12" Voice coil lows 3" 1 x compression tweeter highs 1" Voice coil compression tweeter highs 1.7"
Type of speaker:	On ceiling/on wall speaker
Color:	Light grey
Dimensions:	Width: 45 cm Depth: 41.5 cm Height: 42 cm
Weight:	19.95 kg

Scope of delivery:

1 x top
 1 x mounting bracket
 1 x user manual
 6 x screw
 1 x safety eyelet
 1 x lid
 8 x washer