

OMNITRONIC ODC-224T Outdoor Column Speaker white

Weather-proof column speaker in aluminium cabinet (2 x 4"), with mount, 65 W RMS

Art. No.: 11036976

GTIN: 4026397718171



Features:

- Intelligible voice and superior sound reproduction
- 2-way system with 2 x 10 cm mid-woofer (4")
- Durable aluminum cabinet with grille
- Power selector switch with 8 ohms operating position
- With mounting bracket
- White aluminum grille with acoustic foam
- Suitable for outdoor use IP56
- For application areas such as: Installation; Trade fair and shop fitting; multi-purpose hall
- Application possibility: Wall mounting

Logistic

EAN / GTIN: 4026397718171

Weight: 8,20 kg

Length: 0.22 m

Width: 0.52 m

Height: 0.20 m

Technical specifications:

IP classification:	IP56
Power:	Program: 130W Rated: 65W RMS (8 ohms) Rated: 60W RMS (100V PA)
Frequency range:	120 - 18000 Hz
Sensitivity:	91 dB (1W/1m)
Max. SPL:	115 dB
Dispersion angle:	100° x 60°
Impedance:	8 ohms; public address systems 100V

Attachment system:	Mounting bracket
Power tapping:	15W; 30W; 60W RMS via selector switch switchable
Connections:	2-pin screw plug connector (M) mounting version IP
Crossover frequency:	1800 Hz
Speaker:	2 x woofer 4" with ferrit magnet Basket material: aluminum Voice coil lows 1" Diaphragmmaterial: mylar 1 x compression tweeter highs 1" with ferrit magnet Voice coil compression tweeter highs 1.4"
Type of speaker:	Column speaker
Type of construction:	Closed Box
Material:	Aluminum
Color:	White
Dimensions:	Width: 12.7 cm Depth: 14.4 cm Height: 44.6 cm
Weight:	7.40 kg

Scope of delivery:

1 x top
2 x angle
1 x plug (male)
10 x washer
4 x screw
1 x user manual