

## OMNITRONIC KB-212A Plastic cab.,active

Active 2-way speaker system for PA and DJ applications

Art. No.: 11038696

GTIN: 4026397425307



### Features:

- Active speaker-system for direct connection with the signal source
- Large mid-range horn
- 2-way crossover
- Mic and line inputs with separate level controls
- Master control with 2-way tone control and clip LED
- Line output for linking further active speaker systems
- Delivery includes brackets for use as floor monitor
- Strong protective grille for perfect protection
- Flange for stand installation
- Carrying handles
- Scratch-resistant plastic housing
- Compact speaker-system for car transport
- Ideal for live music or for permanent installation in party rooms
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

EAN / GTIN: 4026397425307

Weight: 19,70 kg

Length: 0.47 m

Width: 0.38 m

Height: 0.65 m

### Technical specifications:

|                  |                                                 |
|------------------|-------------------------------------------------|
| Power supply:    | 115/230 V AC, 50/60 Hz                          |
| Output power:    | Max. 300 W                                      |
| Frequency range: | 50 - 18000 Hz                                   |
| Dimensions:      | Width: 58 cm<br>Depth: 48 cm<br>Height: 32.5 cm |

|                         |                                         |
|-------------------------|-----------------------------------------|
| Weight:                 | 18 kg                                   |
| Rated power:            | 150 W RMS                               |
| Program power:          | 300 W                                   |
| Components:             | 30 cm woofer (12"), 3.5 cm horn (1.35") |
| Inputs:                 |                                         |
| Mic:                    | 3-pin XLR or 6.3 mm jack, bal.          |
| Line:                   | 3-pin XLR, bal. or stereo RCA           |
| Outputs:                |                                         |
| Line:                   | 3-pin XLR or 6.3 mm jack, bal.          |
| Maximum SPL:            | 115 dB                                  |
| Dimensions (H x W x D): | 580 x 480 x 325 mm                      |

**Scope of delivery:**