

OMNITRONIC ACS-410BTS Active Column Speaker System

Mobile column PA system with stereo Bluetooth link, 410 W

Art. No.: 11038866

GTIN: 4026397613452



The article is no longer in our assortment.

Description:

The ACS-410BTS is an active column PA system with a high-power subwoofer with 2-channel class D amplifier module and a full-range column speaker for mobile applications. The system offers two mono inputs (XLR and 6.3 mm jack) for microphones and line sources, one stereo input (RCA and 6.3 mm jack), as well as one AUX input for portable audio players. You can stream music wirelessly from your mobile devices via Bluetooth. The amplifier supplies a power of 310 W and 100 W and is protected with a limiter against overload. The column speaker mounts on top of the subwoofer with the included telescope bar. The integrated stereo Bluetooth link allows for wireless stereo operation with 2 systems linked together.

Logistic

EAN / GTIN: 4026397613452

Weight: 19,75 kg

Length: 0.65 m

Width: 0.49 m

Height: 0.43 m

Features:

- Highly portable column PA system with 410 watts power
- Clear, dynamic sound and wide coverage for DJs, musicians, presenters and events
- Stereo Bluetooth link for wireless stereo operation with 2 systems linked together
- 10" bassreflex subwoofer with class D amplifiers (310 W + 100 W)
- Column speaker with 6 x 2" drivers
- Integrated Bluetooth audio streaming
- Built-in 6-channel mixer
- 2 mono inputs mic/line with 2-band EQ and adjustable reverb
- 1 stereo line input
- 1 stereo AUX input connects any non-Bluetooth device
- Volume control per channel
- Adjustable monitor output
- Master level control with limiter indication
- Subwoofer with M20 threaded flange and locking features for secure transport of column speaker and distance tube

- MDF enclosures with scratch-resistant lacquer surface, impact-resistant steel grille and carry handles
- Total weight just 18 kg
- Delivery includes variable distance tube, speaker cable and power cable
- Control via Bluetooth

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	400 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Rated: 100W RMS HF Rated: 310W RMS LF
Frequency range:	45 - 20000 Hz
Control:	Bluetooth
Connections:	Output: speaker via speaker built-in socket (F) Output: line via RCA (F) mounting version Input: line via 1 x stereo RCA Input: line via 2 x 6.3 mm jack socket (stereo) mounting version Input: mic/line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: AUX via 1 x 3.5 mm jack (stereo) mounting version
Input channels:	2 x stereo with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial 1 x stereo via jack, channel control via rotary dial 1 x stereo via RCA or jack plug, channel control via rotary dial
Crossover frequency:	220 Hz
Speaker:	1 x woofer 10" 6 x tweeter 2"
Dimensions:	Width: 33.5 cm Depth: 41 cm Height: 57 cm
Weight:	18.10 kg

Scope of delivery:

- 1 x power cord
- 1 x speaker cable
- 1 x bass
- 1 x top
- 1 x stand
- 1 x user manual