

OMNITRONIC BOB-10A Subwoofer active black

10" subwoofer with DSP and Bluetooth for the BOB series

Art. No.: 11038870

GTIN: 4026397650167



Features:

- 10" bassreflex subwoofer with DSP and 900 watts RMS power
- Flexibly extendable with BOB-4 satellites for 2.1, 4.1 and 8.1 configurations
- DSP-controlled class D amplifier (300 W + 2 x 300 W)
- Signal inputs via combo jacks (XLR/6.3 mm jack) and RCA
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE; SPEECH
- The device is cooled by passive convection cooling
- Control via Bluetooth
- Bluetooth: operating range up to 10m in buildings
- Black metal grille with acoustic foam
- 4 Rugged carrying handles
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

Logistic

EAN / GTIN: 4026397650167

Weight: 18,15 kg

Length: 0.52 m

Width: 0.35 m

Height: 0.50 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 1060 W

Protection class: Protection class I

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Power:	Rated: 1x 300W RMS LF Rated: 2x 300W RMS HF
Frequency range:	45 - 250 Hz
Sensitivity:	100 dB
Max. SPL:	125 dB
DSP:	Digital signal processor
DSP presets:	FLAT; DJ; LIVE; SPEECH
Cooling:	Passive convection cooling
Control:	Bluetooth
Bluetooth device name:	Omnitronic BOB
Range:	Bluetooth: range up to 10m in buildings
Attachment system:	2x M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch
Controls:	Softstart; short-circuit; limiter; Overvoltage; overheat; limiter
Status LED:	Signal, power, limit, fault, DSP presets
Connections:	Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: speaker via 2 x speaker built-in socket (F) Output: line via 2 x 3-pin XLR
Input channels:	1 x stereo via combination socket or RCA or Bluetooth, channel control via rotary dial
Speaker:	1 x woofer 10" Basket material: steel Conematerial: cardboard/paper Voice coil lows 2"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	4 pc/pcs
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating
Dimensions:	Width: 30 cm Depth: 47 cm Height: 43 cm
Weight:	16.95 kg
Cable length:	3 m

Scope of delivery:

1 x bass
 1 x user manual
 1 x power cord
 2 x speaker cable
 4 x foot
 4 x screw
 1 x declaration of conformity