

OMNITRONIC PAM-150 Active PA system

Portable 120 W PA system

Art. No.: 11038885

GTIN: 4026397203691



The article is no longer in our assortment.

Description:

A full success as ideal PA-system for professional promotion events "on the road" or for hobby promotion shows

Features:

- PA system with 4-channel mixer, power amplifier and integrated 2-way speaker-system
- Easy transportation via 2 wheels and telescopic trolley-handle
- Ideal for all mains independent and wireless applications like seminars, conferences, presentations, tradeshow, fashion shows, solo entertainers, weddings, sales booths, aerobics etc.
- Power supply either via 230 V, internal rechargeable batteries or car battery
- Delivery includes 5 meter connection cable for cigarette lighter
- Connection of up to two cabled mics
- Mic input via XLR/jack socket on the top panel
- Switchable and adjustable echo effect for mic channels
- Connection of further line signals via two stereo channels (RCA or jack), e.g. for playing back multimedia applications from PC, laptop or portable MP3 player
- Integrated 5-band equalizer for fine-tuned sound
- 25 cm woofer (10") included
- Line output for connecting further components
- Speaker output for connecting external speaker-system (switches internal speakers off)
- Impact-resistant steel grille

Logistic

EAN / GTIN: 4026397203691

Weight: 21,95 kg

Length: 0.40 m

Width: 0.35 m

Height: 0.66 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	120.00 W
Output power:	Max. 120 W
Frequency range:	65 - 20000 Hz
Dimensions:	Width: 59 cm Depth: 36 cm Height: 28 cm
Weight:	20.57 kg
General:	
	or 12 V DC via built-in lead gel rechargeable battery or external car battery
Battery operation:	2-4 hours
Recharging time:	7-10 hours
Dimensions (H x W x D):	590 x 360 x 280 mm
Control unit:	
Inputs:	
2 mono	XLR or balanced 6.3 mm jacks
2 stereo	RCA or 6.3 mm jacks
Outputs:	
1 Main Out:	balanced 6.3 mm jack
1 Speaker Out	balanced 6.3 mm jack
Speaker-system:	
Rated power:	60 W RMS
Program power:	120 W
Components:	25 cm woofer (10"), 2.5 cm horn (1")
Sensitivity:	94 dB
Impedance:	8 ohms
Amplifier:	
Nominal power output:	60 W RMS / 8 ohms
Maximum power output:	120 W / 8 ohms
Distortion:	0.05 %
S/N-ratio:	>90 dB

Scope of delivery: