

OMNITRONIC MOLLY-12A Subwoofer active black

Active 12" subwoofer with DSP and Bluetooth

Art. No.: 11039050

GTIN: 4026397680119



List price: 641.41 €

incl. 19% VAT.

Features:

- 12" bassreflex subwoofer with DSP and 700 watts RMS power
- Flexibly extendable with MOLLY-6 satellites for 2.1 and 4.1 configurations
- DSP-controlled class D amplifier (500 W + 2 x 100 W)
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE; VOICE
- The device is cooled by temperature-controlled fan
- Control via Bluetooth
- Operating range up to 10m
- Black metal grille with acoustic foam
- 2 Rugged carrying handles
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

Logistic

EAN / GTIN: 4026397680119

Weight: 24,60 kg

Length: 0.62 m

Width: 0.52 m

Height: 0.47 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 1000 W

Protection class: Protection class I

Output power: 1 x 500 W RMS
2 x 100 W RMS (8 ohms)
2 x 200 W RMS (4 ohms)

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Frequency range:	40 - 160 Hz
Sensitivity:	103 dB
Max. SPL:	128 dB
DSP:	Digital signal processor
DSP presets:	FLAT; DJ; LIVE; VOICE
Cooling:	Temperature-controlled fan
Control:	Bluetooth
Bluetooth device name:	Omnitronic
Range:	Range up to 10m
Attachment system:	Flange: M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch, level control per channel, power switch, connect
Controls:	Softstart; short-circuit; limiter; Overvoltage; overheat
Status LED:	Signal, power, limit, fault, DSP presets
Connections:	Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x 3.5 mm jack (stereo) mounting version Input: line via 1 x stereo RCA Output: line via 2 x 3-pin XLR Output: top via 2 x speaker built-in socket (F)
Input channels:	1 x stereo via combination socket or RCA or Bluetooth, channel control via rotary dial
Speaker:	1 x woofer 12" Basket material: steel Conematerial: cardboard/paper Voice coil lows 3"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	2 pc/pcs
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 47 cm Depth: 57 cm Height: 40 cm
Weight:	22.85 kg
Cable length:	3 m

Scope of delivery:

1 x bass
 1 x power cord
 2 x speaker cable
 1 x user manual
 1 x declaration of conformity